

Pendelleuchte | 220-240 V | 1xE27

CA022AWHEZZ



Technische Daten	
Typ	Pendelleuchte
Installationsposition	Decke
Installationsumgebung	Indoor
Leuchtmittel inbegriffen	Nein
Anschluss der Leuchte	1 x E27 Max 22W
Optik	Diffuses
Light emission direction	downward
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehrbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	3 m
Harzbeschichtung	Nein
Nettogewicht	1 Kg

Oberfläche Gehäuse	
Material	Aluminium - Aluminium - Aluminium - Aluminium
Farbe	Text white Ral 9003 - Text white Ral 9003 - Text white Ral
Bearbeitungstyp	Lackierung - Lackierung - Lackierung - Lackierung

Oberfläche fassung	
Material	Eisen - Eisen - Eisen - Eisen
Farbe	Text white Ral 9003 - Text white Ral 9003 - Text white Ral
Bearbeitungstyp	Lackierung - Lackierung - Lackierung - Lackierung

Cables Electrification+suspension	
Max. Kabellänge	3000 mm

Pendelleuchte | 220-240 V | 1xE27
CA022AWHEZZ

Single emission pendant luminaires for indoor application. Compatibility:
LED lamp; lamp cap 1xE27.

The device body is made of aluminium and features a text white ral 9003 finish, processed by means of coating The device body is made of aluminium and features a text white ral 9003 finish, processed by means of coating The device body is made of aluminium and features a text white ral 9003 finish, processed by means of coating The device body is made of aluminium and features a text white ral 9003 finish, processed by means of coating The device body is made of aluminium and features a text white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a text white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a text white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a text white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a text white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a text white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a text white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1 kg.

The power supply cable is included and features a 3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.