

PRODUCT NO. 3666-060120

DOTLUX LED-Akkustrahler WORKERmini 20W 6500K 7,4V



to the product page

- Adjustable, glare-free light surfaces for homogeneous illumination with latching function.
- Extremely compact, impact-resistant (IK08) and splash-proof (IP65) plastic housing
- Ergonomic carrying handle with integrated metal tripod mount
- Dimmable in three brightness levels with battery charge indicator
 - 30% light output = 9 Hours
 - 50% light output = 6 Hours
 - 100% light output = 3 Hours
 - (Charging time max. 5 hours)
- Charging cable included for car/truck 12/24 V and 220 V
- Conveniently replaceable, integrated lithium-ion rechargeable battery
- Continuous operation via 220 V charging cable at full brightness level possible

WEIGHT IN KG	1.58
POWER CONSUMPTION IN WATTS	20
CONSUMPTION (KWH/1000H)	20
NET LUMINOUS FLUX IN LUMENS	1900
LUMEN PER WATT	95

Dimensions

length: 324mm
width: 180mm
height: 90mm

BEAM ANGLE	120°
CAPACITY OF BATTERY IN MAH	8800
DIMMABLE	Step dimming
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE	220-240 V AC
ENERGY EFFICIENCY 2019/2015	F
COLOR TEMPERATURE IN KELVIN	6500
COLOR-RENDERING-INDEX	CRI > 82
WARRANTY	3 years
IK PROTECTION	IK07
L/B VALUE	L80/B10
LIFETIME	approx. 40.000 h at 25°C
LIGHT COLOR	daylight white
COVER MATERIAL	Polycarbonate PC
HOUSING MATERIAL	Impact-resistant plastic
SWITCH CYCLES	> 80.000
IP-PROTECION	IP65
PROTECTION CLASS	III
ASSORTMENT	Proline
TEMPERATURE RANGE	0°C to +40°C