



SONIC centric pole free standing DIRECT / INDIRECT

059-7921677P

PROJECT

TYPE

NOTES

QUANTITY

DATE

GENERAL

Floor
Standing
white
IP20
indirect 5500 lm
direct 5250 lm
total 10750 lm
RAL9010^a

LED

4000 K
CRI ≥ 80
L90 / 50000 h
photobio. safety RG 0 - no Risk

OPTICAL

Microprismatic

PHYSICAL

Centric Pole 2050 mm
diameter 500 mm
height 2102 mm
20 kg

ELECTRICAL



daylight & movement sensor
71 W
151 lm/W
PC1 220-240V

^a RAL Palette colors may deviate slightly due to production conditions.



Free standing luminaire with conical luminaire head in die-cast aluminium; round pedestal with recess for table stand; round aluminium upright tube aligned centre; surface white powder coated; direct/indirect illumination characteristic; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; indirect component covered with clear acrylic glass; direct lighting portion: micro prismatic PMMA cover; perfectly uniform illumination through use of a diffuse polycarbonate-based film; better light dispersion to transparency ratio; light colour 4000 K; Binning initial ≤ 3 MacAdam; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; luminaire with integrated infrared presence and brightness sensor; automatic light control for individually adjustable brightness; variable automatic shutdown; easy adjustment by integrated miniature push-button; presence sensor detection range ø4,5m on the floor; incl. connection cable (3m) with safety plug; sound absorbing accessories available: patented soundproofing element made of expanded polystyrene (EPS);

Light Distribution





SONIC centric pole free standing DIRECT / INDIRECT

059-7921677P

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	31
B16	50
B20	62
B25	78
C10	52
C16	85
C20	104
C25	130

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Other

ABSORBER

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
bazalt grey	bazalt grey	∅1280·72	9 5 9 - 6 9 9 9 1 1 6
light grey	light grey	∅1280·72	9 5 9 - 6 9 9 9 1 1 7