

# Anoli Spot Pendant

The spotlight consists of a drop-formed cylindrical body in powder-coated or anodized metal, designed for either pendant or surface mounting. The fixture provides a focused, directional light. The spotlight uses a single GU10 light source positioned centrally within the body. Cable included for the wall and pendant versions.

Designed by **Sofie Refer**

|                         |  |  |  |
|-------------------------|--|--|--|
| <b>Product no.</b>      | 2013008 - black / black<br>black textile cord<br>2013009 - nordic gold / white<br>brass textile cord   | <b>Dimensions</b>  | 290mm x ø100mm<br>Cable length: max 2.500mm  |
| <b>Materials</b>        | Metal / Fabric   |  |  |
| <b>Canopy</b>           | Not included   |  |  |
| <b>Cleaning</b>         | Use only soft dry or dampened cloth. Do not use any detergents.  |  |  |
| <b>Environment</b>      | Indoor   |  |  |
| <b>Certifications</b>   | CE, UKCA, Class II, IP20   | <b>Weight</b>  | 360g   |
| <b>Light source</b>     | GU10, max 10W (Not included)<br><br>Light source can be added to delivery on request or via our webshop at nuura.com.<br><br>See our light source guide on nuura.com.  | <b>Packaging</b>   | Dimensions: L:125mm x W:125mm x H:320mm<br>Weight: 180g<br>Total weight incl. product: 540g<br>Number of parcels: 1<br>Material: Brown cardboard |
| <b>Photometrics</b>     | Depends on the light source.<br><br>LDT/IES lighting files with recommended light sources available on nuura.com.  | <b>Colours</b>   |   |
| <b>Electrical</b>       | Input voltage: 220-240Vac / 50-60Hz  |  |  |
| <b>Lighting control</b> | Dimming is possible with a dimming module compatible with your lighting control system and a compatible light source.<br><br>All Nuura light sources can be dimmed with most common trailing-edge LED dimmers.<br><br>An appropriate dimmer module can be included upon request. |  |  |