

HOOD MINI Pendant

Design by Form Us With Love



Specifications

Article number
L2010A1D

Luminaire
Hood mini 600x600

Colour
Light grey

CRI/CT
830

Control
Touch and DALI

Size (mm)
L600xW600xH305mm

Light output
950lm

Power
23W

IP Rating
20

SDCM
3

Electrical Class
1

General information

Material

Shades in molded polyester felt.

PRO: Luminaire housing in aluminium. Diffuser in opal acrylic.

E27: Body in spun aluminum.

Installation

PRO: Suspended in 2.5 m wire, height adjustable.

E27: Suspended in connection cable.

Connection

PRO: 2.5m black halogen free connection cable 5x1 mm² with free leads. 0.75 m black halogen free cable 5x1 mm² with quick connectors for through wiring. Delivered with or without black ceiling cup.

E27: 3 m black halogen free textile cable 2x0.75 mm². Black ceiling cup with terminal block 2x2.5 mm².

Light source

PRO: Including LED light source, colour temperature 2700K, 3000K or 4000K. Colour rendering: CRI 80 (CRI 90 on request). Lifespan L90B10 100 000h. Calculated according to TM-21: L95 100 000h.

E27: Is delivered without light source. Recommended light source is available as an accessory and is compatible with a variety of dimmers (see list of dimmers). Recommended dimmer is compatible with Schneider Electric Trend and Exxact frame available as accessory. Lifespan L70 25 000h for recommended light source.

Driver

PRO: DALI/DSI driver that regulates the light with amplitude modulation creating a flicker-free light. Dimming 1-100%. The programmed light settings remain, even after power cut. SwitchDim and CorridorFunction possible. Lifespan: 100 000hrs.

Weight

PRO

600x600: 1,9 kg

600x1200: 3,6 kg

600x1800: 5,3 kg

600x2400: 7,0 kg

600x3000: 8,7 kg E27

600x600: 0,9 kg

Measurements

