




## CONCRETO M

WL, recessed wall light grey, 8.5W, 350lm, 3000K


The concrete CONCRETO M wall-mounted light adds a fresh touch to outdoor areas. With a colour temperature of 3000 Kelvin, the integrated LED bulb emits a very pleasant, warm white light with a particularly sustainable lifespan of 50,000 hours. Thanks to the IP65 protection class rating, the grey concrete light is ideally protected against penetration by dirt or moisture.



## TECHNICAL DATA

Item no.	1006404
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	8.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,38
Number of luminaires at LS B16A	92
Number of luminaires at LS C16A	92
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Temperature at glass (light emission)	46 °C
Lumen	270 lm
Colour temperature	3000 Kelvin
Color	grey
CRI	80

## Light Source

1319289		<b>LXXBXX data</b>	L80B50
		<b>Service life</b>	50000 h
		<b>Risk Group</b>	0
		<b>Width</b>	25 cm
		<b>Height</b>	15 cm
		<b>Depth</b>	8 cm
		<b>Net weight</b>	3 kg
		<b>Gross weight</b>	3.21 kg