

Additional comments

Technical Data Sheet

| _ | 1 001 | Toominaal Bata Shoot | | |
|-----------------|--|---------------------------------------|---|--|
| Product number | 61185-1BK | Professional image / Primary image | Technical 2D/3D Line Drawing with Measurements | |
| Date: | 17/11/2025 | | | |
| Product range | Wales | | | |
| Product name | Wales LED Wall Light, Matt Black Metal with Marble Resin | | | |
| Application | - | | | |
| Barcode | 5053423301150 | | | |
| Product Details | Base Details | | | |

| Darcoue | | 3033423301130 | | | |
|--|---------------|--------------------------------|---------------------------------------|-------------------------|----------------------|
| Product Details | | Base Details | | | |
| Primary material | Mild Steel | | Base dimensions (mm) | | |
| Secondary material | Resin | | Light details | | • |
| Colour | Black | | Primary lamp holder | | LED |
| Finish | Painted Matt | | Primary lamp holder number of lamps | | 1 |
| Total height (mm) | 350 | | Primary lamp type | | Integrated LED |
| Height (mm) | 350 | | Primary lamp included | | Yes - Integrated Led |
| Width (mm) | 65 | | Secondary lamp holder | | - |
| Length (mm) | | | Secondary lamp holder number of lamps | | |
| Projection (mm) | 100 | | Secondary lamp type | | - |
| Shade/glass/diffuser colour | Black and Wi | nite | Primary lamp lumens | | 639 |
| Shade/glass/diffuser finish | Marble Effect | | Secondary lamp lumens | | |
| Shade/glass/diffuser material | Resin | | Class | | 2 (Double Insulated) |
| Shade/glass/diffuser style | Cylinder | | Colour temperature (K) | | 3000 |
| Cut out (mm) | | | CRI | | >82 |
| Recess depth (mm) | | | Beam angle (degrees) | | |
| Fire rated | - | | Electrical details | | • |
| IP rating | IP44 | | Primary lamp wattage | | 13W |
| Bathroom zones | - | | Secondary lamp wattage | | |
| Tilt angle (degrees) | - | | Operating voltage | | 220-240V~50/60Hz |
| Height adjustable | No | | Transformer/driver details | | LED driver |
| Adjustable details | No | | Dimmable | | - |
| Max drop for ceiling fittings (mm) | | | Dimming method | | Triac Dimmable |
| Minimum drop for ceiling fittings (mm) | | | Switched | | No |
| Energy class | G | | Switch location | | - |
| Warranty details | | Led Lighting - 5 Year Warranty | Switch type | | - |
| Efficacy (Im/w) | , megrates | | Plug details | | - |
| Ceiling cup / Back plate details | | Supply cable total length (mm) | | | |
| Ceiling cup dimensions (mm) | I | | Supply cable colour | | - |
| Ceiling cup details | | | Chain length from ceiling cu | o to lampholder (mm) | |
| Ceiling cup shape | - | | Supply cable length from bas | se/lampholder to switch | |
| Ceiling cup colour | - | | Supply cable length from sw | itch to plug (mm) | |
| Ceiling cup finish | - | | Packaging details | | · |
| Ceiling cup material | - | | Unit box height (metres) | | 0.16 |
| Ceiling cup fixing | - | | Unit box length (metres) | | 0.42 |
| Wall back plate dimensions (mm) | L150 X W60 | X H40 | Unit box width (metres) | | 0.17 |
| Wall back plate shape | Rectangle | | Unit box net weight (kg) | | 0.83 |
| Wall back plate colour | Black | | Unit box gross weight (kg) | | 1.24 |
| Wall back plate finish | Painted Matt | | | | 1 |
| Wall back plate material | Mild Steel | | | | |
| Wall back plate fixing | Screw | | | | |
| | | | 1 | | |

(Default)