



LUCE SFERICA S1 EU/CCC

Designed byRonan Bouroullec, 2025



Main Information


|                          |   |
|--------------------------|---|
| Ean                      | 8059607075685   |
| Custom product           | No  |
| Location                 | Indoor  |
| Environment              | Indoor dry location                                   |
| Mounting                 | Suspension  |
| Light source type        | LED   |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| LED type                 | LED Module  |
| System flux (lm)         | 5,345   |

Downloads

Mounting instructions PDF ↕

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Optical

|                       |                  |
|-----------------------|------------------|
| Lighting type         | Indirect, Direct |
| Optical type          | Diffused light   |
| Lighting distribution | Symmetric        |

Electrical

|                          |   |
|--------------------------|---|
| Frequency (Hz)           | 50/60   |
| Power supply             | Integrated  |
| Power supply type        | Dimmer on board                                       |
| Power supply replaceable | Replaceable control gear by a professional            |
| Insulation Class         | I   |
| Main voltage (Vac)       | 100-240   |
| Dimming                  | Yes   |
| Power (W)                | 110   |
| LED current (mA)         | 500   |
| Power factor (W)         | 0.95  |
| Dimming interface        | Dimmer Integrated                                     |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| Light source type        | LED   |
| LED type                 | LED Module  |
| CCT (K)                  | 2700  |
| System flux (lm)         | 5,345   |
| LOR (%)                  | 100   |
| CRI                      | 95  |

Physical

|   |                        |
|---|------------------------|
| Suspension type   | Suspension steel cable |
| Cord length (mm)  | 2700                   |
| Cord length (in)  | 106.299                |
| Canopy length/diameter (mm)                                   | 900                    |
| Canopy length/diameter (in)                                   | 35.433                 |
| template.product.physical.canopy.widtd class="table-lable"    | 78                     |
| template.product.physical.canopy.widtd class="table-lable".us | 3.071                  |

Logistic

|                            |       |
|----------------------------|-------|
| Net weight (kg)            | 27.95 |
| Net weight (lb)            | 61.62 |
| Gross weight (kg)          | 35.2  |
| Gross weight (lb)          | 77.6  |
| Shipping packages quantity | 3     |

Marking

|              |    |
|--------------|----|
| IP Category  | 20 |
| Energy Label | F  |
| Casambi      | No |