

Light Sources Technical Datasheet


General Functionality Information			
Mains light source	☒ MLS	☐ NMLS	
Connected light source	☐ CLS	☒ NCLS	
Colour-tuneable light source	☐ CTLS	☒ NCTLS	
Directional light source	☐ DLS	☒ NDLS	
High luminance light source(Y/N)		N	
Dimmable (Y/N)		N	
3-steps dimming		-	
Sensor/IR/BLE/WIFI/433MHz etc.		-	

Lighting Technology			
☒ LED	☐ OLED	☐ Halogen tungsten	☐ Incandescent
☐ LFL	☐ CFLi	☐ CFLni	☐ HPS
☐ QMH	☐ CMH	☐ Other:	

Mechanical Features			
Lamp cap (Socket)	E27		
Lamp type (Shape)	A60		
Lamp envelope	☐ Second envelope		☒ Non-clear envelope
	☐ Clear envelope		☐ Anti-glare shield
	☐ Non-envelope		☐ Other:
Outer dimensions (mm)	Height	107±2	Depth 60±1
	Length		Width 60±1
Mass (g)	24±10%		

Electrical Features	
Rated voltage (V)	220-240V~ 50/60Hz
Nominal current (mA)	32mA
Nominal wattage (W)	5.9
Full load on-mode power (P _{on} , W)	5.9
Displacement factor DF (PF)	0.5
Standby power (P _{sb} , W)	-
Networked standby power (P _{net} , W)	-

Flicker Metric & Stroboscopic Effect Metric	
PstLM	0.1
SVM	0.1

Light & Colour	
Color temperature (k)	3000K
Color Temperature (in words)	warm white
Color rendering index (CRI)	90
R9	0
Color consistency for LED (CCI)	6-step
Chromaticity coordinates (x,y)	x=0.440 y=0.403
Spectral power distribution in the range 250nm to 800nm at full-load	

Lifetime & Lumen Maintenance	
L _{70B50} (h)	25000
Lumen Maintenance Factor @3000h	95.81%
Lamp Survival Factor @3000h	≥90%

	Article Number	
	11932	
	Trade mark	EGLO
	First production date	
	Still in production (Y/N)	Y
Supplier	Sky-lighting	
Supplier item no.	A60-LIC 5.9W 3000K	
Certification		
Supplier Warranty		

Light Emitted Features	
Nominal lumen (lm)	806
Rated useful lumen(360°/120°/90°)	806(360°)
Calculated Pon max (W)	9.43
Directional light(Y/N)	N
Peak luminous intensity (cd)	-
Beam angle (°)	-
Equivalent power(W)	60
Kelvin/Lumen	3000K/806lm

Energy Efficiency Label (EEL)	
Regulation No.	(EU) 2019/2015
Energy efficiency class (EEL)	D
Energy efficiency (lm/W)	136.61
Applicable factor F _{TM}	1
Energy consumption (kWh/1000h)	6
QR-code	

Application & Temperature	
Ambient temperature (°C)	25
Outdoor or Industrial use (Y/N)	N

Mercury	
Mercury inside (x,x mg)	0
Instructions for mercury (Y/N)	N

Recycling	
☒ WEEE - Recycling Icon	☐ Recycling Weblink

Testing information	
Reference report No.	Sky-lighting data
Test Lab.	-
Testing specifications	-
Date of sample received	-

Release	
Release by / Date	Gigi /2023-07-04
Signature	

