

PRODUCT NO. 4559-030360

DOTLUX LED bollard light WAY 55cm 7,5/15W 3000K



to the product page

Dotlux LED bollard light WAY 55 cm

- Free choice of light emission surface due to interchangeable glass and cover plates
- Power-Select allows adjustment of system power 50% / 100%
- High-quality aluminium housing with powder coating in DB703
- Rugged, splash-proof design for outdoor use with IP 54 protection
- Glare-free and homogeneous light distribution with high colour rendering Ra>82
- EasyMount platform enables quick and easy installation
- For loop-through with connection box (input and output each for 3 x 4 mm² cable)
- Mounting base made of special aluminium alloy, approved for installation with earth contact

WEIGHT IN KG	2.85
POWER CONSUMPTION IN WATTS	7.5-15
NET LUMINOUS FLUX IN LUMENS	400/800
LUMEN PER WATT	53

BEAM ANGLE	360°
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE	176-240V AC/DC
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
WARRANTY	5 years
HOUSING COLOUR	gray
IK PROTECTION	IK06
L/B VALUE	L80/B10
LIFETIME	approx. 40.000 h at 25°C
MATERIAL	Aluminium
IP-PROTECION	IP65
ASSORTMENT	Proline
TEMPERATURE RANGE	-25°C to +45°C

Dimensions

length: 120mm
width: 120mm
height: 550mm