



SLC SmartOne Power Supply CV 24V 75W TW Zigbee

14/01/2022

S32055



Product description

Tunable White 24V, 75W PSU with built-in PWM dimmer
 Based on the latest Zigbee 3.0 protocol
 Works stand-alone when connecting a push switch or wirelessly via TouchLink to a remote control / switch
 Supports TouchLink communication with Zigbee remote controls and switches
 Compatible with most smart home systems

Technical data

Model	Static
Dimming with push-button	Yes
Suitable for constant voltage	Yes
Output current	- 3120 mA
Degree of protection (IP)	IP20
Length	244 mm
Height	32 mm
Number of LED Output Channels	4
Mono	Yes
Input voltage (V)	100 - 277
Power factor	0,95
Strain relief	Yes
Operating temperature	-20°C ~ +45°C
Tc (°C)	85

Dimming Zigbee	Yes
Housing	Plastic housing
Output voltage	24 - 24 V
Output power	75 - 75 W
Protection class	II
Width	64 mm
Output type	Constant voltage (CV)
Output power per channel (W)	-
Tunable White	Yes
Frequency range (Hz)	50 - 60
Inrush Current (A)	2
Exterior color	White
Expected lifetime (Hours) (Ta 45°C)	50000





Dimming interface	PushDim, Zigbee
Dimming range	0-100%
Produced by	The Light Group

Dimming method	Pulse Width Modulation (PWM)
Dimming curve (LED)	Logarithmic
Brand	SLC
HS Code	85041080