


MINIROOLER 48VDC 17W 3000K CRI90 DALI 50°

Code: 472-019BV-30

Fixed miniaturized linear track light for 48VDC tracks, featuring 15 high-efficiency LEDs of the latest generation and PMMA microlenses. Thanks to its small dimensions, Miniroller can be an invisible presence within the 14mm gap of 48VDC tracks and 35 Track. Miniroller grants high lighting performance, low glare levels and homogeneous light distribution. This track light can be used in combination with other ARIA's 48VDC track light tools, for a highly versatile and performing use of the light, and for a greatest freedom of application in residential, contract, hospitality spaces and offices.



General specifications

Designer	Ivela Design Team
Commercial brand	Miniroller
Installation environment	Interior
Native mounting type	Track mounted
Mounting type	Track attachment
Ideal application locations	Residential, Hospitality, Showroom, Museum, Office, Commercial space
Made in	Italy

Physical specifications

Shape	Rectangular
Body material	Aluminum
Body finish	Matte
Body color	Black
Frontal material	Aluminum
Frontal finish	Matte
Frontal color	Black
Thermal dissipation	Passive
IP	IP20

Lighting specifications

N° of light sources	1
Lumen	1320
L.O.R. (%)	81
Nominal Lumen	1650
Power	17
Light type	White
CCT	3000K
CRI	90
SDCM	3
RG	RG1
Life time	L80B10
LB value @ h	50000

Optical specifications

Emission type	Direct monoemission
Light beam distribution	Symmetric
Beam	50
Optics type	Symmetrical optical lens
Optical diffuser finish	Transparent
Optical diffuser material	PMMA
Orientability	Fixed

Electrical specifications

Power supply availability	Not included
Power supply position	Remote
CV / CC converter availability	Included
CV / CC converter position	Internal
Dimmable	Yes
Dimmer availability	Not included
Dimming type	DALI Dimming
Dimmer position	Remote
Power supply voltage type	DC
Power supply type	Voltage
Input Voltage (V)	48
Insulation class	III
Light source type	LED COB
Replaceable light source	Replaceable by skilled personnel

Dimensions and weight

Length (mm)	468
-------------	-----

Width (mm)	14
------------	----

General conditions

Warranty	5 years
----------	---------
