## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Nordlux

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2070062701

## Type of light source:

| Lighting technology used:     | LED | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|-----|---------------------------------|------|--|--|--|
| Light source cap-type         | E27 |                                 |      |  |  |  |
| (or other electric interface) |     |                                 |      |  |  |  |
| Mains or non-mains:           | MLS | Connected light source (CLS):   | No   |  |  |  |
| Colour-tuneable light source: | No  | Envelope:                       | -    |  |  |  |
| High luminance light source:  | No  |                                 |      |  |  |  |
| Anti-glare shield:            | No  | Dimmable:                       | No   |  |  |  |
| Product parameters            |     |                                 |      |  |  |  |

| Product parameters                   |  |                         |   |              |  |  |  |
|--------------------------------------|--|-------------------------|---|--------------|--|--|--|
| Parameter                            |  | Value                   | Parameter   | Value        |  |  |  |
| General product parameters:          |  |                         |   |              |  |  |  |
|                                      | mption in on-<br>100 h), rounded<br>st integer                             | 7                       | Energy efficiency<br>class  | E            |  |  |  |
| indicating if it r<br>in a sphere (3 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 900 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 6 500        |  |  |  |
| On-mode p<br>expressed in W          | oower (P <sub>on</sub> ),  | 7,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |  |
| for CLS, expre                       | ndby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal          | -                       | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |  |
| Outer<br>dimensions<br>without       | Height   | 109                     | Spectral power  | See image    |  |  |  |
|                                      | Width  | 60                      | distribution in the   | in last page |  |  |  |
|                                      | Depth  | 60                      | 1   | Page 1/:     |  |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre)       |      | range 250 nm to 800<br>nm, at full-load  |                |  |  |  |
|--|------|--|----------------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | Yes  | If yes, equivalent power (W)             | 66             |  |  |  |
|  |      | Chromaticity<br>coordinates (x and y)    | 0,312<br>0,328 |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |                |  |  |  |
| R9 colour rendering index value  | 6    | Survival factor                          | 0,90           |  |  |  |
| the lumen maintenance factor   | 0,93 |  |                |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |                |  |  |  |
| displacement factor (cos φ1)   | 0,84 | Colour consistency<br>in McAdam ellipses | 6              |  |  |  |
| Claims that an LED light<br>source replaces a fluorescent<br>light source without integrated<br>ballast of a particular wattage. | _(b) | lf yes then<br>replacement claim<br>(W)  | -              |  |  |  |
| Flicker metric (Pst LM)  | 0,0  | Stroboscopic effect<br>metric (SVM)      | 0,0            |  |  |  |

(a)'-' : not applicable;

(b)'\_-' : not applicable;

