
Honey

Wall Lights | 220-240 V | topLED 20 W DC 500 mA CRI 90 8690 [f][< c 🙀 🕱 🗘 🛓 c.c. 🗁 🖭





Technical data	
Construction year	2019
Туре	Wall Lights
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	20 W
Source lumens	2076 lm
Frequency	60 - 50 Hz
CCT / Tone	2700 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	Phase cut
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	2,195 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casi	ng
Material	Iron
Colour	embossed white RAL 9003
Finishing diffu	Iser
Material	PC
Colour	white

Honey

Wall Lights | 220-240 V | topLED 20 W DC 500 mA | CRI 90 8690

Double emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 72 topled LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 2076 lm, with a 103.8 lm/W nominal luminous efficacy.

The device body is made of iron and features a embossed white ral 9003 finish; the diffuser is made of PC. The ingress protection degree is IP20; the total weight is of 2,195 kg.

The total absorbed power is 20 W.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

2076 lm
2700 K
3 Step MacAdam
90 Ra
80
25

Honey

Honey | Wall Lights | Accessories 8690

	Dimmer 220-240V	Code KIT0026
CASAAGI III. Niii	Dimmer Radio-frequenza, 85-240V	Code KIT0080