






Button HL

by Piero Lissoni , 2004



Wall/ceiling fixture providing diffused lighting for indoor use. Hand-blown opal ply glass diffuser (transparent – opal – transparent) with acid finish. Sheared, deep-drawn steel sheet wall/ceiling attachment with white galvanized finish. Sheared, deep-drawn steel sheet reflector painted white for high temperatures. Closing cover in injection molded tecnopolymer with chrome finish. Satin-finish incandescent line voltage halogen lamps.



| | |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting | Ceiling and wall |
| Environment | Indoor |
| Weight | 13.5 Kg |
| Light sources available | 5 x LED 3W G9 290lm 2700K [e] cod. 28425 Non dimmable 5 x LED 2W G9 240lm 2700K cod. RF26520 [e] No Dimmable |
| Emergency | Without |
| Switching | Luminosity can be adjusted by means of traditional dimmers installed in the recessed versions. |
| Voltage | 220-250V |
| Power | 5x MAX 40W |
| Battery | No |
| Supply included | Yes |
| Materials | Glass |
| Colors | ● F3190009 - White |
| Certificate |      |

