

MICROPERFETTO 48V 26W 30K DALI 30° BI

Code: 754-889-21

Low-voltage 48V electrified track spotlight designed for high-efficiency COB LEDs. It is equipped with reflector.



General specifications

Designer	Ivela Design Team
Commercial brand	Microperpetto
Installation environment	Interior
Native mounting type	Track mounted
Mounting type	Track attachment
Ideal application locations	Residential, Hospitality, Showroom, Museum, Office, Commercial space
Wire incandescent test	850
Made in	Italy

Physical specifications

Shape	Cylindrical
Body material	Aluminum
Body finish	Matte
Body color	White
Frontal material	Aluminum
Frontal finish	Matte
Thermal dissipation	Passive
IP	IP20

Lighting specifications

N° of light sources	1
Lumen	1890
Power	26

Light type	White
CCT	3000K
CRI	90
SDCM	3
RG	RG1
Life time	L80B10
LB value @ h	50000

Optical specifications

Emission type	Direct monoemission
Beam	30
Optics type	Symmetrical optical lens
Optical diffuser finish	Transparent
Orientability	Adjustable
Rotation degrees	355
Swivel degrees (°)	90

Electrical specifications

Dimmable	Yes
Dimming type	DALI Dimming
Power supply voltage type	DC
Power supply type	Voltage
Input Voltage (V)	48
Insulation class	III
Light source type	LED COB
Energy efficiency class	E
Replaceable power supply system	Replaceable by skilled personnel
Replaceable light source	Replaceable by skilled personnel

Dimensions and weight

Length (mm)	116
Width (mm)	210
Diameter (mm)	53

General conditions

Warranty	5 years
----------	---------