





Luminaires

Hersteller	ICONE
Article number	SALSOLA 48MO-OU1
Product name	SALSOLA
Product group	freestanding uplighter
Mounting type	Surface mounted
Mounting place	Floor
Designer	Marco Pagnoncelli
Test mark	C€

Model / Variant / Configuration

Number / Name BI

Description

white

Luminaires

Efficiency	80.15%
System Light flux	1442.70 Lm
Luminaire output	57.70 Lm/W
LiTG class	C12
CIE flux codes	12 36 68 41 82
System power	25.0W
Protection class	Protection class II
Protection degree	IP 54

Powered by © Relux Page 1

Dimensions

	Diameter/Height	480mm/480mm		
Light Source				
	Lamp type	1 x Compact fluorescent lamp		
	ZVEI / ILCOS	TCR-SER / FBC		
	socket	E27		
	Lamp power	25 W		
	System power	25 W		
	Light flux	1800 lm		
	Colour temperature	ww/2700K		
	Colour rendering	1B		
	Lifetime	10000 h		

Description

Repositionable outdoor floor or table lamp (MO) IP55 rating, available with aluminium structure only and white (BI), old brown (OB) finish.

Complete with power cable (mt. 5) and IP44 plug.

SALSOLA OUTSIDE products are treated with anti-corrosive coatings.

A protective undercoat, tested for 700 hrs in saline fog and a colour finish, tested for 240 hrs in saline fog, ensure these products an extremely long life.

The products may vary slightly in size due to the fact that they are manufactured predominantly by hand.

Energy class A++, A+, A, B, C, D, E

Powered by © Relux Page 2