


# LED Spot GU10 6W / LED Spot GU10 6W




- An = 100%
- 1x = 60%
- 2x = 40%
- 3x = 15%



WEEE Nr. 85761858

## Abmessungen (mm) Dimensions (mm)



Hoher CRI Wert +, fsvwvuzfz [^Sdnatural light, High luminous efficacy, Long life-span, Flicker free

- Vollspektrum LED's
- Hohe Lichtausbeute 90 / 100 lm/W (+/- 5%)
- Hoher CRI Wert Ra ≥ 95
- Sockel GU10
- Applikationen:  
Haushalt, Büro, Hotel, Gewerbe
- Beste naturgetreue Farbwiedergabe
- Flickerfrei
- 3-Klick-Dimmverfahren 100 % / 40 % / 15 %

### Spezifikationen

Produkt	
Nennleistung	6 W (+/- 5%)
Abmessungen	∅ 50 x 57 mm
Farbtemperatur	2.700 K / 4.000 K (+/- 5%)
Farbwiedergabeindex	Ra ≥95
Nennlichtstrom	~ 600 / 650 lm / W (+/- 5%)
Effizienz	~ 90 / 100 lm / W (+/- 5%)
Gewicht	35 g
Lebensdauer	> 30,000 hours
Betriebsspannung	AC 230 V @ 50 Hz / 60 Hz
Gehäusematerial	UL94-5VA
Betriebstemperatur	-20 °C ~ +40 °C
3-Klick-Dimmung	100% / 40% / 15%

High CRI +, Vskvuzfz eL [^Sdnatural light, High luminous efficacy, Long life-span, Flicker free

- fullspectrum LED's
- Luminous efficacy 90 / 100 lm/W (+/- 5%)
- High CRI Ra ≥ 95, High-visibility light
- Base GU10
- Applications:  
Home, Commercial, Hotel, Gallery, Business
- High color reproduction
- Flickerfree
- 3-click-dimming 100 % / 40 % / 15 %

### Specifications

Products	
Power Consumed	6 W (+/- 5%)
Size	∅ 50 x 57 mm
CCT	2.700 K / 4.000 K (+/- 5%)
CRI	Ra ≥95
Total Lumen	~ 600 / 650 lm / W (+/- 5%)
Efficacy	~ 90 / 100 lm / W (+/- 5%)
Weight	35 g
Life-span	> 30,000 hours
Input Voltage	AC 230 V @ 50 Hz / 60 Hz
Body (Heat Sink)	UL94-5VA
Operating Temperature	-20 °C ~ +40 °C
3-click-dimming	100% / 40% / 15%


**ENERGY**  
euroLighting GmbH  
LED Spot - GU 10 - 2700K

6 kWh/1000h

**ENERGY**  
euroLighting GmbH  
LED Spot - GU 10 - 4000K

6 kWh/1000h

### Lichtverteilungskurve Light Distribution Curve



### Lichtspektrum / Light spectrum

Bei CCT 4000K / at CCT 4000K

