PC PENDANT

PRODUCT FACT SHEET





PC PENDANT

DESIGN BY PIERRE CHARPIN, 2019

Pierre Charpin's PC Pendants is a collection of refined suspension lighting that can be used independently or clustered together. The pendants are constructed in anodised aluminium, which makes the surface more resistant to corrosion. The light source in each pendant lamp is hidden by a removable polycarbonate moulded diffuser, creating both a soft directional output of light and determining the form of the lamp itself. The PC Pendants are available in a variety of sizes and colours, and are suitable for both contract and domestic markets.


ı 103 +

41 [


HIGHLIGHTS

- · Part of a progressive and technologically advanced lighting collection.
- · A family of refined pendants, task lights, table and portable lamps.
- ·CE approved.
- · Designed for use with a replaceable standard retro fit LED dimmable bulb.
- ·The fitting can be used in conjunction with a number of standard wall mounted dimming control units.
- · Suitable for both private and office environments.


DIMENSIONS








MEDIUM WIDTH 40 CM | 15.7" DEPTH 40 CM | 15.7" HEIGHT 20,5 CM | 8.1"





LARGE WIDTH 60 CM | 23.6" DEPTH 60 CM | 23.6" HEIGHT 28 CM | 11"

MATERIALS

HEIGHT 14,5 CM | 5.7

SHADE
Anodised spun aluminium shade.

DIFFUSER

Injection moulded translucent polycarbonate diffuser.

CABLE

Braided fabric cable with a PVC insulation.

Please note that the cable is black for all colour options.

COLOUR & FINISH

Please note that the colour codes are indicative.

SHELL	SIZE	SMALL	MEDIUM	LARGE		
SOFT BLACK RAL 9004		•	•	•		
EMERALD GREEN RAL 6002		•	•			
BLUSH RED PANTONE 492 U		•				
ALUMINIUM ANODISED		•	•	•		

PC PENDANT SMALL

TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	RECOMMENDED POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
3 x LED G9	3-5W (max. 5W)	Yes**	220-240V AC at 50-60Hz	400 cm	No

^{*}Bulb not included.

TEST SPECIFICATIONS*


FLUX (LUMENS)

CCT (KELVIN) & CRI (1-100)

300-600lm

The levels will vary depending on the type of bulb used in the lamp.


PHOTOMETRICS



CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.



Tested according to the following european EN IEC standards which relate specifically to electrical lighting products including

- · EN 55015:2013 (radio disturbance)
- · EN 61547:2009 (EMC immunity)
- ·EN 61000-3-2:2014 (EMC compatibility)
- ·EN 61000-3-3:2013 (EMC compatibility)
- · EN 60598-2-4:1997 (portable luminaires)
- · EN 60598-1:2015 (general requirements)
- ·EN 62493:2010 (human exposure to EMC)

COUNTRY OF ORIGIN

China

DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Image Bank at hay.com.

LINK TO IMAGE BANK

^{**}If used in conjunction with a wall mounted dimmer and suitable LED bulb.

^{*}Photometrics and the specification shown is taken using the recommended LED bulb fitted in the production luminaire.

PC PENDANT MEDIUM

TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	RECOMMENDED POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
1 x LED E27 (A19)	10-13W (max. 13W)	Yes**	220-240V AC at 50-60Hz	400 cm	No

^{*}Bulb not included.


TEST SPECIFICATIONS*

FLUX (LUMENS)

CCT (KELVIN) & CRI (1-100)

The levels will vary depending on the type of bulb used in the lamp.


PHOTOMETRICS



CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.



Tested according to the following european EN IEC standards which relate specifically to electrical lighting products including

- · EN 55015:2013 (radio disturbance)
- · EN 61547:2009 (EMC immunity)
- ·EN 61000-3-2:2014 (EMC compatibility)
- ·EN 61000-3-3:2013 (EMC compatibility)
- EN 60598-2-4:1997 (portable luminaires)
- · EN 60598-1:2015 (general requirements)
- ·EN 62493:2010 (human exposure to EMC)

COUNTRY OF ORIGIN

China

DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Image Bank at hay.com.

LINK TO IMAGE BANK

^{**}If used in conjunction with a wall mounted dimmer and suitable LED bulb.

^{*}Photometrics and the specification shown is taken using the recommended LED bulb fitted in the production luminaire.

PC PENDANT LARGE

TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	RECOMMENDED POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
3 x LED E27 (A19)	10-13W (max. 13W)	Yes**	220-240V AC at 50-60Hz	400 cm	No

^{*}Bulb not included.


TEST SPECIFICATIONS*

FLUX (LUMENS)

CCT (KELVIN) & CRI (1-100)

The levels will vary depending on the type of bulb used in the lamp.


PHOTOMETRICS



CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.



Tested according to the following european EN IEC standards which relate specifically to electrical lighting products including

- · EN 55015:2013 (radio disturbance)
- · EN 61547:2009 (EMC immunity)
- ·EN 61000-3-2:2014 (EMC compatibility)
- ·EN 61000-3-3:2013 (EMC compatibility)
- EN 60598-2-4:1997 (portable luminaires)
- · EN 60598-1:2015 (general requirements)
- · EN 62493:2010 (human exposure to EMC)

COUNTRY OF ORIGIN

China

DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Image Bank at hay.com.

LINK TO IMAGE BANK

^{**}If used in conjunction with a wall mounted dimmer and suitable LED bulb.

^{*}Photometrics and the specification shown is taken using the recommended LED bulb fitted in the production luminaire.