MOUNTING INSTRUCTIONS FOR CEILING AND WALL LAMPS BY FERRO LUCE

ATTENTION: Read the instructions carefully before starting to assemble.

The operational safety of the lighting fixture is only given for installation by the specialist, functional use and compliance with the regulations for maintenance. Keep these instructions for assembly. The installation of this lighting fixture may only be carried out by qualified personnel. The manufacturer disclaims any responsibility should the standards described here not be followed

- 1- For installation or maintenance of the lighting fixture, disconnect the ceiling connection from the power by turning off the main switch (fuse).
- 2- Since you need to assemble a mounting bracket (**Photo 2**) / mounting plate (**Photo 1**), protect the power cable and do not damage the insulation.
- 3- Remove the mounting plate (or mounting bracket) (**Photo 3 and 4**) from the lighting fixture by loosening the two side screws.
- 4- Attach the mounting plate (or mounting bracket) in the immediate vicinity of the power cable with screws and, if necessary, dowels (both not included). Attention! Be careful not to damage the insulation of the power cable.
- 5- Open the plastic cable box (**Photo 5**). Loosen the outer insulation of the external house cable by approx. 8 cm and guide the cables through the black rubber insulation.
- 6- Connect brown, sky blue and green/yellow cables from the external house cable with lighting fixture in the plastic cable box. Please, pay attention to the colours and symbols specified in the cable box:
 - L = Live = brown cable (right)
 - N = Neutral = sky blue cable (left)
 - T = Earth green and yellow cable (in the middle) Photo 5
- 7- Close the cable box.
- 8- Position the cable box in the opening of the ceiling or/and in the mounting box of the lighting fixture (Photo 3 and 4)
- 9- Slightly lower the screws in the mounting plate (or mounting bracket), slide the body (mounting box of lighting fixture) over the mounting plate (or mounting bracket) so that you can lock it with a slight left / right turn. (Photo 3 and 4)
- 10- For this purpose, a recess in the mounting box of lighting fixture is provided specifically. Now tighten the screws.
- 11- Screw in light bulbs (not included) and switch the ceiling connection over the fuse back to voltage.







Foto 1

Foto 2

Foto 3





Foto 4

Foto 5