



Table lamp for indirect lighting with a 18,8 W LED source. Light intensity is adjustable through a rotating dimmer. Aluminium structure with transparent glass diffuser.

Finishing

Standard

Anodised black
cod. 14001X000

Anodised brass
cod. 14050X000

All RAL coating and galvanic finishes available upon request

Light emission

- Light emission: diffuse
- Light direction: indirect downlight
- Light source: led board
- Source flux: 1500 lm
- Emitted flux: 315 lm
- Efficacy: 17 lm/W
- CCT: 3000K
- CRI index: >97
- Lifetime: >55000h L80 @ 25°C

Electrical Facts

- Source power: 18 W
- Power absorption: 18,5 W
- Stand-by absorption: < 1 W
- Grid voltage: 100-240V AC/50-60Hz
- Power supply: multiplug AC-DC converter provided
- Dimmability: internal dimmer with rotating interface
- Energy class: A++

Technical data

- Environment: indoor
- Placement: table
- Net weight: 5,6 Kg
- Certifications: CE
- Suggested ambient T: 25°C
- Maximum ambient T: 40°C
- Insulation class: III
- Protection class: IP20

Packaging
cardboard box
27 x 27 x 47 (cm)
0,04 m³

Gross weight
7,2 Kg

