

Luminaire


Code 2060010APP
Name RIPPLE 50 SOSPENSIONE APP

Measurem.

Code FTS2000798
Name RIPPLE 50 SOSPENSIONE APP

Luminaire Flux	3110.00 lm	Luminaire Power	50.00 W	Efficacy	62.20 lm/W	Efficiency	100.00%
Lamps Flux	3110.00 lm	Maximum value	352.31 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area	Diam. 500 mm Diam. 300 mm	Height	30 mm	Height	0 mm		
Horizontal Luminous Area	0.070686 m ²	Emitting area on Plane 180°	0.000000 m ²				
Emitting area on Plane 0°	0.000000 m ²	Emitting area on Plane 270°	0.000000 m ²				
Emitting area on Plane 90°	0.000000 m ²	Glare area at 76°	0.017100 m ²				
Coordinate system	CG	Symmetry Type	Rotosymmetrical				
Date	22-09-2020	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	3110.00 lm				
LED Flux=6300lm LED Power=47W Eff=49% EfcLed=134lm/W EfcLum=62lm/W CCT=3000 Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	47 79 96 100 100	D DIN 5040	A30				
F UTE	1.00 E	B NBN	BZ 5 / 2 / BZ 4				

Diam=500mm




Semipiani C

180.0 ——— 0.0

ULOR 0.02 %

DLOR 99.98 %

RN 0.02 %



Luminaire

Code 2060010APP
Name RIPPLE 50 SOSPENSIONE APP

Measurement


Code FTS2000798
Name RIPPLE 50 SOSPENSIONE APP

Luminaire Flux	3110.00 lm	Luminaire Power	50.00 W	Efficacy	62.20 lm/W	Efficiency	100.00%
Lamps Flux	3110.00 lm	Maximum value	352.31 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	500 mm	Height	30 mm		
Round Luminous Area		Diam.	300 mm	Height	0 mm		
Horizontal Luminous Area		0.070686 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.017100 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		22-09-2020		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3110.00 lm	
LED Flux=6300lm LED Power=47W Eff=49% EfcLed=134lm/W EfcLum=62lm/W CCT=3000 Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	47 79 96 100 100			D DIN 5040	A30		
F UTE	1.00 E			B NBN	BZ 5 / 2 / BZ 4		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.48	2.96	4.45	5.93	7.41	OC	1.48	2.96	4.45	5.93	7.41
OB	1.48	2.96	4.45	5.93	7.41	OD	1.48	2.96	4.45	5.93	7.41

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1095.68	1090.21	1048.03	970.24	860.30	723.45	564.64	388.86	206.01	50.04
OB	1095.68	1090.21	1048.03	970.24	860.30	723.45	564.64	388.86	206.01	50.04
OC	1095.68	1090.21	1048.03	970.24	860.30	723.45	564.64	388.86	206.01	50.04
OD	1095.68	1090.21	1048.03	970.24	860.30	723.45	564.64	388.86	206.01	50.04



H[m]	D[m]	Max lux	Med lux	Alpha=56.0°+56.0°	G=0.0
1.00	2.96	1096	268		
2.00	5.93	274	67		
3.00	8.89	122	30		
4.00	11.86	68	17		
5.00	14.82	44	11		