

BOX

14-Dec.-2016

1.0 LED

LED 8W | 220-240VAC | 50-60Hz | COB 2-step | incl. PS | phase-cut dim

CE IP20 0,3m 36° P

white texture	146164W
aluminium brushed	146164L
gold	146164G
bronze	146164Q
copper	146164P
black texture	146164B

LIGHT COLOUR

2700K >80CRI 600lm	2
3000K >80CRI 600lm	4
1800-2850K >90CRI 410lm	9

1.0 PAR16

PAR16 max. 35W | GU10 | 100-240VAC | 50-60Hz

CE IP20 0,9m

white texture	146120W0
aluminium brushed	146120L0
gold	146120G0
bronze	146120Q0
copper	146120P0
black texture	146120B0

OPTIONAL

for PAR16 lamps see our catalogue

OPTIONAL

single inner reflector max. 10W



white texture	911211W1
gold	911211G1
black texture	911211B1

OPTIONAL

single inner cover max. 10W


white texture	911011W1
gold	911011G1
black texture	911011B1

base plate dimensions




1.0 LED


1.0 PAR16



DIMENSIONS



1.0 LED




1.0 PAR16

1 MOUNTING INSTRUCTION

Remove the screws of the top part, put the cables through the opening and mount the base on the ceiling.

2 POWER CONNECTION

Connect wiring to the power supply (for LED) or to terminal block (for PAR16)
interior connection: STANDARD version



STANDARD

3 FOR LED

Attach the LED housing on the base by two socket screws.

4 FOR LED

Attach the box cover to the LED housing by screwing the locking ring

FOR PAR16

Attach the box cover to the base by screwing the locking ring

5 OPTIONAL inner reflector

Attach the reflector to the box cover by screwing the locking ring.

with inner reflector: **max. 10W**

6 OPTIONAL inner cover

put the inner cover in the outer cover by screwing.

with inner cover: **max. 10W**



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

Wever & Ducre bvba Kwadestraat 153 bus 2.1 8800 Roeselare

INSTALLATION
INSTRUCTIONS

PAGE 1/2

BOX

14-Dec.-2016

1.0 LED

LED 8W | 220-240VAC | 50-60Hz | COB 2-step | incl. PS | phase-cut dim

CE IP65 10.3m 36° P

white texture	735164W_
dark grey texture	735164D_
black texture	735164B_

LIGHT COLOUR

3000K >80CRI 600lm	4
1800-2850K >90CRI 410lm	9

OPTIONAL

single inner reflector max. 10W


white texture	911211W1
dark grey texture	911211D1
black texture	911211B1

OPTIONAL

single inner cover max. 10W


white texture	911011W1
dark grey texture	911011D1
black texture	911011B1

base plate dimensions




1.0 LED


①



③




④




or

⑤




or

⑥



DIMENSIONS




1.0 LED

① MOUNTING INSTRUCTION

Remove the screws of the top part, put the cables through the opening and mount the base on the ceiling.

② POWER CONNECTION

Connect wiring to the power supply
exterior connection: WATERPROOF version (only for LED)



③ Attach the LED housing on the base by two socket screws.

④ Attach the box cover to the LED housing by screwing the locking ring

⑤ **OPTIONAL inner reflector**
Attach the reflector to the box cover by screwing the locking ring.

With inner reflector: **max. 10W**

⑥ **OPTIONAL inner cover**
put the inner cover in the outer cover by screwing.
with inner cover: **max. 10W**



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

Wever & Ducre bvba Kwadestraat 153 bus 2.1 8800 Roeselare

**INSTALLATION
INSTRUCTIONS**

PAGE 2/2