GRAU

## Love Focus

Love Focus ist der flexible Scheinwerfer aus hochwertigem Aluminium. Mit einstellbaren Abstrahlwinkel setzt der leistungsstarke Strahler ein Bild, Objekt oder eine Wand brillant in Szene.

Mit einer einfachen Drehung am Leuchtenkopf, kann der Lichtkegel fokussiert werden.

Love Focus bietet eine Reihe von cleveren Funktionen:

- Einstellbarer Abstrahlwinkel
- Dimmer an der Leuchte
- Powder Skin Oberfläche

Designed und gefertigt am GRAU Campus in Deutschland.

## Farben

| Farben | Artikelnummer |
|---|---|
| Black | CPO79-1 |
| White | CPO79-3 |

## Dimensionen



## Body

| | |
|---|---|
| Maße Verpackung (L x B x H) | 35cm x 25cm x 10cm |
| Material | Aluminium |
| Oberfläche | Pulverbeschichtet |
| Gewicht | 1kg |
| Gewicht inkl. Verpackung | 1,5kg |
| Leuchtenkopf beweglich | Ja |
| Montageart | Freistehend |
| Nennspannung | 220–240 V |
| Leistungsaufnahme | 12W |
| Leuchteneffizienz | 37lm/W – 41lm/W |
| Länge Anschlussleitung | 2,8m |
| Steckernetzteil | Ja |
| Schutzklasse | II |
| Artikelnummer | CPO79-1 |

## Licht

| | |
|---|---|
| Leuchtmittel | LED |
| Leuchtenlichtstrom | 420–470lm |
| Farbwiedergabeindex | CRI >90 |
| Lichtaustritt | Direkt |
| Abstrahlwinkel | 15–80° |
| Lichtverteilung | Symmetrisch |
| Farbtemperatur | 2700K |
| Lichtfarbe | Warmweiß |
| Dimmbar | Ja |
| Art der Dimmung | Integrierter Taster |
| Warm Dim | Ja |

GRAU

## Love Focus

Love Focus is the flexible spotlight made of high-quality aluminum. With an adjustable beam angle, the powerful spotlight brilliantly highlights a picture, object or wall.

The light beam can be focused with a simple turn of the lamp head.

Love Focus offers a range of clever functions:

- Adjustable beam angle
- Dimmer on the luminaire
- Powder Skin surface

Designed and manufactured at the GRAU Campus in Germany.

## Colors

| Colors | SKU |
| --- | --- |
| Black | CPO79-1 |
| White | CPO79-3 |

## Dimensions




Head
ø 9 cm

## Body

| | |
|---|---|
| Packaging dimensions (L x W x H) | 35cm x 25cm x 10cm |
| Material | Aluminum |
| Surface | Powder-coated |
| Weight | 1kg |
| Weight incl. packaging | 1,5kg |
| Movable lamp head | Yes |
| Mounting type | Floor |
| Rated voltage | 220–240 V |
| Power consumption | 12W |
| Luminaire efficiency | 37lm/w - 41lm/w |
| Length of connection cable | 2.8m |
| Plug-in power supply unit | Yes |
| Protection class | II |
| SKU | CPO79-1 |

## Light

| | |
|---|---|
| Light source | LED |
| Luminous flux | 420–470LM |
| Color rendering index | CRI >90 |
| Light emission | Direct |
| Beam angle | 15–80 ° |
| Light distribution | Symmetric |
| Color temperature | 2700–2200K |
| Light color | Warm White |
| Dimmable | Yes |
| Type of dimming | Integrated pushbutton |
| Warm Dim | Yes |