




## MOBALA

### Indoor recessed wall light 3000K white

Aluminium recessed wall light MOBALA WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The MOBALA recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	1002982
IP Code	IP 20
Assembly	Recessed
Assembly details	Wall
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	24 V
Safety class	II
Wattage	1.3 W
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0
Lumen	14 lm
Colour temperature	3000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	asymmetric
Light outlet	direct
Risk Group	0
Width	9 cm
Height	9 cm
Depth	4.5 cm

## Light Source

916574	
--------	---

## Accessories

1002984	MOBALA WL , installation frame
1002983	MOBALA WL , installation box

Net weight	0.137 kg
Gross weight	0.195 kg
Shape of cut-out	square
Installation length	7.8 cm
Installation width	7.8 cm
Installation depth	6 cm
BIG WHITE Page	243