





LED STRIP COB CV 512 5M 8MM 11W 1200LM 940 IP54

S14058

Product description

Special LED strip designed to achieve even light

512 LEDs each meter make it easy to create a uniform line of light, even when using a low aluminium profile

Special LED strip designed to achieve even light

512 LEDs each meter make it easy to create a uniform line of light, even when using a low aluminium profile High CRI 90+ With double-sided 3M 300LSE tape, the strip is versatile and easy to install Should be placed in profile for cooling, this to ensure longevity

Technical data

Model	Strip
Lamp type	LED not exchangeable
Lamp power per meter	11 W
Voltage type	DC
Beam angle	120 °
Rated life time L70/B10 at 25 °C	54000 h
Protection class	II
Colour of light	White
Colour rendering index CRI	90-100
Height/depth	2 mm
Length of particular segments	31,25 mm
With protective cover	Yes

Mounting method	Surface mounting/recessed mounting
Number of nodes per meter	512
Luminous flux per meter	1200 lm
Lamp voltage	24 - 24 V
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP54
Max. system power	55 W
Colour temperature	4000 - K
Width	8,4 mm
Length	5000 mm
With end piece	Yes
Self-adhesive	Yes



THE LIGHT GROUP GmbH Am Schafbrinke 62 | 30519 Hannover | Germany Tel.: +49 (0)511 - 807 486 10 | E-Mail: info@tlg.no

THE LIGHT GROUP AS Sagmyra 2A, 4624 | Kristiansand S | Norway Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no



The Light Group Datasheet



Type of wiring	Ending
Conductor cross section	0,5 mm²
Cutting point, every: (mm)	31
3M adhesive tape	Yes
Produced by	The Light Group

LED-Strip length (m) 5 Max length per connection: 5 meter Brand SLC HS Code 94054010	Number of poles	2
Brand SLC	LED-Strip length (m)	5
	Max length per connection:	5 meter
HS Code 94054010	Brand	SLC
	HS Code	94054010

