SLC LED STRIP TW CV 168 10M 10MM 12,5W 1375LM 827/65 IP

14/01/2022

S14050

Product description

Tunable White technology is a good solution, whenever standard white colour temperatures are not enough. This LED-strip combines 2 types of diodes: 2400K and 6500K, which gives a Tunable white light. 10 meters on one single connection.

Tunable White technology is a good solution, whenever standard white colour temperatures are not enough. This LED-strip combines 2 types of diodes: 2400K and 6500K, which gives a tunable white light spectre. Changing light temperature from ultra warm 2400K to day-like 6500K will modify rooms ambient. Adjust light colour temperature as you desire with our user friendly stand-alone controls, which fit any installation. Suitable in any solution, as direct, decorative and background light. 168 LED diodes per meter give smooth and uniform linear light. Shall be installed in aluminum profiles, to ensure sufficient cooling and long product lifetime. 10 meter on a single connection.

Technical data

Model	Strip	Mounting method	Surface mounting/recessed mounting
Lamp type	LED not exchangeable	Number of nodes per meter	168
Lamp power per meter	12,5 W	Luminous flux per meter	1375 lm
Voltage type	DC	Lamp voltage	24 - 24 V
Beam angle	120 °	Type of control gear	LED operating device voltage-controlled
Rated life time L80/B10 at 25 °C	60000 h	Degree of protection (IP)	IP20
Protection class	II	Max. system power	125 W
Colour of light	White	Colour temperature	2700 - 6500 K
Colour rendering index CRI	80-89	Power factor	0,95
Width	10 mm	Height/depth	1,6 mm
Length	10000 mm	Length of particular segments	71,4 mm
With connection set	Yes	Type of wiring	Ending
Number of poles	3	Conductor cross section	0,35 mm²

The Light Group

THE LIGHT GROUP GmbH
Am Schafbrinke 62 | 30519 Hannover | Germany
Tel.: +49 (0)511 - 807 486 10 | E-Mail: info@tlg.no

THE LIGHT GROUP AS
Sagmyra 2A, 4624 | Kristiansand S | Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no

LED-Strip length (m)	10	**Max length per connection:**	10 meter
Operating temperature	-20°C ~ +45°C	**3M adhesive tape**	Yes
Dimming method	Pulse Width Modulation (PWM)	**Dimmable**	Yes
Dimming range	1-100%		