

PRODUCT NO. 4931-0FW120

DOTLUX LED Aufbauleuchte SURFACE dali Ø400x62 30W 3000/4000/5700K COLORselect weiß



to the product page

- DALI dimmable version
- Quick and easy mounting with EASYbase base plate and twistlock fastener
- Wide product variety enables use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable design, LED module, power supply unit and battery can be replaced without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact-resistant polycarbonate housing IK10
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor use
- Individual light colour adjustable with COLORselect (light colour: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery

WEIGHT IN KG	1.6
NET LUMINOUS FLUX IN LUMENS	2850-3000
POWER CONSUMPTION IN WATTS	30
CONSUMPTION (KWH/1000H)	30
LUMEN PER WATT	max. 100

Dimensions

height: 62mm
diameter: 400mm

BEAM ANGLE	120°
DIMMABLE	DALI
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE	176-240V AC/DC
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
FREQUENCY RANGE IN HZ	50/60
WARRANTY	5 years
HOUSING COLOUR	white
IK PROTECTION	IK10
LIFETIME	approx. 50.000 h at 25°C
LIGHT COLOR	warm white/neutral white/daylight white
MATERIAL	plastic
COVER MATERIAL	Polycarbonate PC
HOUSING MATERIAL	Polycarbonate
POWER SUPPLY	Integrated
SUITED FOR EMERGENCY POWER	Yes
POWER FACTOR	0,9
IP-PROTECION	IP54
PROTECTION CLASS	II
ASSORTMENT	Proline
VOLTAGE TYPE	AC
TEMPERATURE RANGE	-20°C to +45°C