



GAVAN MINI LED ceiling surface-mounted luminaire, IP65, on/off switchable

Article no. 32034073

Light.
For Generations.**Tender**

LED ceiling surface-mounted luminaire, IP65, on/off switchable, Round. Luminaire diameter 320.0 mm, Hight 70.0 mm Weight 0.945 kg, with rotationssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a plastic, opal cover. Luminous flux 1.710 lm, Power 1 x 18 W, System Efficiency 95 lm/W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50000 h,, Colour: White, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP65, shock resistance according to IEC62262: IK10 . With electronic driver, on/off switchable.

Product Benefits

- Ceiling surface mounted luminaire made of impact resistant plastic in diameter of 320 mm, mounting height 70 mm.
- Luminous flux 1710 lm, IK10, IP65, housing made of PMMA plastic.
- 3 different diameters available in the same optical look.
- This allows the realization of the projects with different lighting requirements in a consistent design.

GAVAN MINI LED ceiling surface-mounted luminaire, IP65, on/off switchable

Article no. 32034073

Light.
For Generations.

Article data	
Article no.	32034073
GTIN	4251433926009
Series name	GAVAN MINI
Short description	LED ceiling surface-mounted luminaire, IP65, on/off switchable
Colour	White
Type of surface	Matt
Shape	Round
Outer diameter	320 mm
Hight	70 mm
Scope of delivery	Incl. converter for connection to the 230-V mains voltage, on/off switchable
Weight	0.945 kg

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	1,710 lm
System efficiency	95 lm/W
Colour rendering	CRI > 80
Beam angle	120°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	18 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	II
Degree of protection	IP65
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50000 h

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Impact resistance	IK10
Material cover	Plastic, opal

Packing data	
Gross weight	1.181 kg
Length of packaging	325 mm
Packaging width	325 mm
Packaging hight	85 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.