

Technical Data Sheet

Product number	23350GR F		
Date:	17/11/2025		
Product range	Cone	Cone	
Product name	Cone Rechargeable Wa	ll Light, Green Metal	1
Application	Indoor Wall	Indoor Wall	
Barcode	5053423302850	5053423302850	
Product Details		Base Details	

Professional image / Primary image Technical 2D/3D Line Drawing with Measurements

Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA	ed .	Base Details Base dimensions Light details Primary lamp hole Primary lamp tole Primary lamp type Primary lamp incl Secondary lamp i	der der number of lamps e luded holder holder number of lamps type nens lumens lumens are (K) rees) ails ttage	na LED 1 Integrated LED Yes - Integrated Led - 81 3 (Low Voltage) 3000 tbc 1.5W Rechargeable USB Connection
Primary material Secondary material Colour Finish Painte Total height (mm) Height (mm) 170 Width (mm) Length (mm) Projection (mm) Shade/glass/diffuser colour Shade/glass/diffuser finish Shade/glass/diffuser material Shade/glass/diffuser style Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details Ceiling cup / Back plate details Ceiling cup details Ceiling cup details N/A Ceiling cup details	ed .	Base dimensions Light details Primary lamp hole Primary lamp hole Primary lamp type Primary lamp incl Secondary lamp is Secondary lamp to Primary lamp lum Secondary lamp to Class Colour temperatu CRI Beam angle (degreen to the primary lamp wat Secondary lamp wat Secondary lamp wat Operating voltage	der der number of lamps e luded holder holder number of lamps type nens lumens lumens are (K) rees) ails ttage	LED 1 Integrated LED Yes - Integrated Led - - 81 3 (Low Voltage) 3000 tbc
Secondary material Colour Greer Finish Painte Total height (mm) Height (mm) 170 Width (mm) 100 Length (mm) Projection (mm) Shade/glass/diffuser colour Shade/glass/diffuser finish NA Shade/glass/diffuser material Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details Efficacy (lm/w) Ceiling cup / Back plate details Ceiling cup details Ceiling cup details	ed .	Light details Primary lamp hole Primary lamp hole Primary lamp type Primary lamp incl Secondary lamp is Secondary lamp to Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degreen lamp lamp lamp lamp lamp lamp lamp lamp	der der number of lamps e luded holder holder number of lamps type nens lumens lumens are (K) rees) ails ttage	LED 1 Integrated LED Yes - Integrated Led - - 81 3 (Low Voltage) 3000 tbc
Colour Finish Painte Finish Painte Total height (mm) 170 Height (mm) 170 Width (mm) 100 Length (mm) 95 Shade/glass/diffuser colour Greer Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated - IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes- Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details	ed .	Primary lamp hole Primary lamp hole Primary lamp type Primary lamp incl Secondary lamp i Secondary lamp t Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp voltage	der number of lamps e luded holder holder number of lamps type hens lumens are (K) rees) ails ttage	1 Integrated LED Yes - Integrated Led 81 3 (Low Voltage) 3000 tbc
Finish Painte Total height (mm) 170 Height (mm) 170 Width (mm) 100 Length (mm) 300 Projection (mm) 95 Shade/glass/diffuser colour Greer Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated - IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details	ed .	Primary lamp hole Primary lamp type Primary lamp incl Secondary lamp i Secondary lamp i Secondary lamp t Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp voltage	der number of lamps e luded holder holder number of lamps type hens lumens are (K) rees) ails ttage	1 Integrated LED Yes - Integrated Led 81 3 (Low Voltage) 3000 tbc
Total height (mm) 170 Height (mm) 170 Width (mm) 100 Length (mm) 95 Shade/glass/diffuser colour Greer Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated - IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes- Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details	1	Primary lamp type Primary lamp incl Secondary lamp i Secondary lamp i Secondary lamp i Primary lamp lum Secondary lamp i Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp i Operating voltage	e luded holder holder number of lamps type hens lumens lumens are (K) rees) ails ttage	Yes - Integrated Led - 81 3 (Low Voltage) 3000 tbc
Height (mm) 170 Width (mm) 100 Length (mm) 300 Projection (mm) 95 Shade/glass/diffuser colour Green Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated - IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Primary lamp incl Secondary lamp I Secondary lamp I Secondary lamp I Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp voltage	luded holder holder number of lamps type hens lumens lumens lire (K) rees) ails ttage	Yes - Integrated Led - 81 3 (Low Voltage) 3000 tbc
Width (mm) 100 Length (mm) 300 Projection (mm) 95 Shade/glass/diffuser colour Greer Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated - IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Secondary lamp I Secondary lamp I Secondary lamp I Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degree Electrical detail Primary lamp wat Secondary lamp voltage	holder number of lamps type nens tumens tre (K) trees) ails trage	- 81 3 (Low Voltage) 3000 tbc
Length (mm) 300 Projection (mm) 95 Shade/glass/diffuser colour Greer Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated - IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Secondary lamp I Secondary lamp tum Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp wat Operating voltage	holder number of lamps type nens tumens tre (K) trees) ails ttage	3 (Low Voltage) 3000 tbc 1.5W
Projection (mm) Shade/glass/diffuser colour Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Secondary lamp to Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degree Electrical deta Primary lamp wat Secondary lamp to Operating voltage	type nens tumens tre (K) trees) ails trage	3 (Low Voltage) 3000 tbc 1.5W
Shade/glass/diffuser colour Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser material Cylind Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Intefficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Primary lamp lum Secondary lamp I Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp wat Operating voltage	rees) ails tage	3 (Low Voltage) 3000 tbc 1.5W
Shade/glass/diffuser finish NA Shade/glass/diffuser material Metal Shade/glass/diffuser style Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Intefficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Secondary lamp I Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp voltage	rees) ails tage	3 (Low Voltage) 3000 tbc 1.5W
Shade/glass/diffuser material Shade/glass/diffuser style Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class Warranty details All Integration of the composition of the ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details	ler	Class Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp voltage	rees) ails tage	3000 tbc
Shade/glass/diffuser style Cylind Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Intefficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A	ler	Colour temperatu CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp voltage	rees) ails tage	3000 tbc
Cut out (mm) Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A	ler	CRI Beam angle (degr Electrical deta Primary lamp wat Secondary lamp wat Operating voltage	rees) ails tage	tbc
Recess depth (mm) Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Integration of the property of the		Beam angle (degr Electrical deta Primary lamp wat Secondary lamp v Operating voltage	ails tage wattage	1.5W
Fire rated IP rating Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Interprocess Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Electrical deta Primary lamp wat Secondary lamp voltage	ails tage wattage	
IP rating IP20 Bathroom zones - Tilt angle (degrees) Height adjustable - Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Intelligence (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Primary lamp wat Secondary lamp v Operating voltage	wattage	
Bathroom zones Tilt angle (degrees) Height adjustable Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Interpretation of the property of the propert		Secondary lamp v	wattage	
Tilt angle (degrees) Height adjustable Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Operating voltage		Pachargaphle LISR Connection
Height adjustable Adjustable details Yes - Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Interpretation (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details			•	Rechargeable LISB Connection
Adjustable details Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Transformer/drive		Rechargeable COD Connection
Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Energy class NA Warranty details Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		. Tallolollilol/allve	er details	Li-ion 18650 ,4000mA,3.7V
Minimum drop for ceiling fittings (mm) Energy class NA Warranty details All Inte Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details	shade section can move	e up Dimmable		-
(mm) Energy class NA Warranty details All Interpretation Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Dimming method		Touch Dimmer
Energy class NA Warranty details All Interference (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Switched		Yes
Warranty details Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details		Switch location		Back Plate
Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) N/A Ceiling cup details	egrated Led Lighting - 5 \	Year Warranty Switch type		Type C4 Touch Switch - On / 25% / 50% / 100% / Of
Ceiling cup dimensions (mm) N/A Ceiling cup details	<u> </u>	Plug details		NA
Ceiling cup dimensions (mm) N/A Ceiling cup details		Supply cable tota	I length (mm)	1200
Ceiling cup details		Supply cable cold	our	Black
Ceiling cup shape		Chain length fron	n ceiling cup to lampholder (mm)	N/A
		1. 1. 2	gth from base/lampholder to switch	
Ceiling cup colour -		Supply cable lend	gth from switch to plug (mm)	
Ceiling cup finish -		Packaging de		
Ceiling cup material		Unit box height (r		0.19
Ceiling cup fixing -		Unit box length (r	·	0.12
Wall back plate dimensions (mm) D:100	*H25mm	Unit box width (m	<u> </u>	0.12
Wall back plate shape Round	t	Unit box net weig	·	0.55
Wall back plate colour Green	1	Unit box gross we	·	0.8
Wall back plate finish Painte	ed	5 30x g; 033 W		
Wall back plate material Metal				
Wall back plate fixing				
Additional comments				