

# FLOS

## BON JOUR UNPLUGGED CHR

Designed by Philippe Starck, 2015



### Main Information


|                          |   |
|--------------------------|---|
| Ean                      | 8059607070994   |
| Custom product           | No  |
| Mounting                 | Table   |
| Light source type        | LED   |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| LED type                 | LED Module  |
| Source flux (lm)         | 150   |
| System flux (lm)         | 150   |

### Downloads

|                       |       |
|-----------------------|-------|
| Mounting instructions | PDF ↓ |
| Spare Parts SVG       | SVG ↓ |

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional

**Optical**

|                       |                |
|-----------------------|----------------|
| Lighting type         | Direct         |
| Optical type          | Diffused light |
| Lighting distribution | Roto symmetric |

**Electrical**

|                           |   |
|---------------------------|---|
| Power supply              | Remote excluded                                       |
| Insulation Class          | III   |
| Main voltage (Vac)        | 5   |
| Dimming                   | Yes   |
| Power (W)                 | 3   |
| Charging min time         | 3   |
| Batteries inside          | Yes   |
| Battery type              | LI-IO   |
| Charging socket/connector | USB-C   |
| Induction recharge QI     | Yes   |
| Charging cycle guaranteed | 500   |
| Dimming interface         | Dimmer Integrated                                     |
| Light source replaceable  | Replaceable (LED only) light source by a professional |
| Light source type         | LED   |
| LED type                  | LED Module  |
| CCT (K)                   | 2200-2700-3000  |
| Source flux (lm)          | 150   |
| System flux (lm)          | 150   |
| LOR (%)                   | 100   |
| LED Life / Failure Ratio  | 30000.000   |
| CRI                       | 90  |

**Physical**

|             |       |
|-------------|-------|
| Height (mm) | 270   |
| Height (in) | 10.63 |

**Logistic**

|                            |       |
|----------------------------|-------|
| Net weight (kg)            | 0.55  |
| Net weight (lb)            | 1.21  |
| Gross weight (kg)          | 0.85  |
| Gross weight (lb)          | 1.87  |
| Shipping packages quantity | 1     |
| Package height (mm)        | 170   |
| Package height (in)        | 6.69  |
| Package width (mm)         | 230   |
| Package width (in)         | 9.06  |
| Package length (mm)        | 375   |
| Package length (in)        | 14.76 |

**Marking**

|              |    |
|--------------|----|
| IP Category  | 20 |
| Energy Label | G  |