

# NEMO

## Luminaire

Code ELP LWW 54  
Name Ellisse Major 66W

## Measurerm.

Code EPMa032019  
Name Ellisse Major 66W

|                            |            |                 |               |                             |               |                    |                    |
|----------------------------|------------|-----------------|---------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux             | 3450.00 lm | Luminaire Power | 66.00 W       | Efficacy                    | 52.27 lm/W    | Efficiency         | 100.00%            |
| Lamps Flux                 | 3450.00 lm | Maximum value   | 361.66 cd/klm | Position                    | C=0.00 G=0.00 | CG                 | Double Symmetrical |
| Rectangular Luminaire      |            | Length          | 1350 mm       | Width                       | 700 mm        | Height             | 20 mm              |
| Rectangular Luminous Area  |            | Length          | 1350 mm       | Width                       | 700 mm        | Height             | 1 mm               |
| Horizontal Luminous Area   |            | 0.945000 m2     |               | Emitting area on Plane 180° |               | 0.001350 m2        |                    |
| Emitting area on Plane 0°  |            | 0.001350 m2     |               | Emitting area on Plane 270° |               | 0.000700 m2        |                    |
| Emitting area on Plane 90° |            | 0.000700 m2     |               | Glare area at 76°           |               | 0.229926 m2        |                    |
| Coordinate system          |            | CG              |               | Symmetry Type               |               | Double Symmetrical |                    |
| Date                       |            | 27-01-2000      |               | Maximum Gamma Angle         |               | 90                 |                    |
| Measurement Distance       |            | 0.00            |               | Measurement Flux            |               | 3450.00 lm         |                    |
| Operator                   |            |                 |               | Source Voltage [V]          |               | 230.00 V           |                    |
| Temperature                |            | 25.00 °C        |               | Source current [A]          |               |                    |                    |
| Humidity                   |            | 60.00 %         |               | Photocell                   |               |                    |                    |
| Notes                      |            |                 |               |                             |               |                    |                    |

| Line   | Code   | Luminaire Lamps | Flux [lm]   | Pow. [W] | Q.ty |
|--------|--------|-----------------|-------------|----------|------|
|        |        |                 |             |          |      |
| C.I.E. | 48     | D DIN 5040      | 3450.00     | 66.00    | 1    |
| F UTE  | 1.00 E | B NBN           | A30<br>BZ 4 |          |      |

