


# PHOTOMETRIC TEST REPORT

---

EDGE 560D LED

astro

LIGHT EFFICIENCY:



OUTPUT: 373 lm

LIGHT QUALITY:



PEAK: 71.5 cd

COLOR TEMPERATURE:



POWER: 14.6 W

PF: 0.83



Tracking number: [n/a](#)

Product name:

Edge 560D LED

Item number:


1352006

Date and time:

04/10/2019 15:47:53

Description:

LED Wall Light




251.3°




CIE 1931  
x: 0.457  
y: 0.405



SPECTRA



POWER





COLOR DETAILS



TM30: 81.8

CRI: 81.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.0	93.5	92.4	78.0	81.3	92.7	79.1	55.4	6.3	85.4	77.3	75.4	84.3	96.6	72.8


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
75.3	77.7	76.4	88.9	92.4	92.6	85.5	89.3	83.0	78.2	79.9	83.3	83.5	75.4	81.1	70.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
76.8	92.6	83.8	77.8	80.4	81.9	81.7	83.5	93.0	90.2	85.4	81.3	80.2	71.1	72.9

CQS: 81.0









COLOR PARAMETERS

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
2704 K	81.7	6.3	81.8	94.2	81.0	0.457	0.405	0.263	0.350	-0.0019


**Rf 81.8**  
Fidelity index Rf

**Rg 94.2**  
Gammut index Rg

Hue Bin	Graphic shifts (%)		
	R <sub>f</sub>	Chroma	Hue
1	75	-12%	2%
2	78	-8%	8%
3	76	-3%	11%
4	89	-2%	4%
5	92	0%	2%
6	93	0%	-2%
7	85	-7%	-5%
8	89	-5%	1%
9	83	-6%	7%
10	78	-3%	13%
11	80	2%	13%
12	83	7%	1%
13	83	4%	-10%
14	75	4%	-18%
15	81	-5%	-9%
16	71	-10%	-17%



BEAM DETAILS



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
4lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
0.4fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
4.3	5.1	7.7	10.9	15.0	20.8	28.7	41.3	50.0	57.2	61.9	66.4	70.9	69.9	59.5	44.8	32.8	22.6	14.3	8.7
100%	119%	180%	254%	351%	486%	671%	964%	1169%	1336%	1446%	1551%	1655%	1633%	1390%	1047%	766%	528%	334%	204%

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
4.3	4.6	5.1	6.0	7.4	9.4	11.9	14.7	17.5	25.8	28.6	13.8	13.5	11.4	9.7	7.9	6.5	6.7	7.5	8.5
100%	107%	120%	141%	172%	220%	279%	343%	410%	603%	667%	323%	314%	266%	227%	184%	153%	155%	175%	199%

Intensities in 180° c-plane


0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
4.3	5.1	7.7	10.9	15.0	20.8	28.7	41.3	50.0	57.2	61.9	66.4	70.9	69.9	59.5	44.8	32.8	22.6	14.3	8.7
100%	119%	180%	254%	351%	486%	671%	964%	1169%	1336%	1446%	1551%	1655%	1633%	1390%	1047%	766%	528%	334%	204%

Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
4.3	4.6	5.1	6.0	7.4	9.4	11.9	14.7	17.5	25.8	28.6	13.8	13.5	11.4	9.7	7.9	6.5	6.7	7.5	8.5
100%	107%	120%	141%	172%	220%	279%	343%	410%	603%	667%	323%	314%	266%	227%	184%	153%	155%	175%	199%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
251.3°	360°	360°	11.6%	4.9%


ISO CANDELA DIAGRAM



10%	0 cd
20%	1 cd
30%	1 cd
40%	2 cd
50%	2 cd
60%	3 cd
70%	3 cd
80%	3 cd
90%	4 cd

**Conditions:**  
 Number of c-planes: 8  
 Candela at center: 4 cd

ISO LUX DIAGRAM



3%	1.28m lx
5%	2.14m lx
10%	4.28m lx
30%	12.8m lx
50%	{LUX_10M50} lx

**Conditions:**  
 Number of c-planes: 8  
 Lux at center: 42.8m lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.


## UGR

## GLARE EVALUATION ACCORDING TO UGR

p Ceiling	70	70	50	50	30	70	70	50	50	30	
p Walls	50	30	50	30	30	50	30	50	30	30	
p Floor	20	20	20	20	20	20	20	20	20	20	
Room size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H 2H	2H	6.3	7.3	7.3	8.3	9.6	2.2	3.1	3.1	4.1	5.4
	3H	11.2	12.1	12.2	13.1	14.5	6.2	7.0	7.1	8.0	9.4
	4H	13.8	14.7	14.8	15.7	17.0	8.5	9.4	9.5	10.4	11.7
	6H	16.7	17.4	17.7	18.5	19.9	11.5	12.2	12.5	13.3	14.7
	8H	18.2	18.9	19.2	19.9	21.3	13.1	13.8	14.1	14.8	16.2
	12H	19.8	20.5	20.9	21.6	23.0	14.7	15.4	15.7	16.5	17.9
4H 2H	2H	7.1	7.9	8.1	8.9	10.3	4.6	5.4	5.6	6.4	7.8
	3H	12.1	12.8	13.1	13.8	15.2	8.4	9.1	9.4	10.1	11.5
	4H	14.9	15.5	15.9	16.6	18.0	10.8	11.4	11.8	12.5	13.9
	6H	17.9	18.5	19.0	19.6	21.0	13.6	14.2	14.7	15.3	16.7
	8H	19.5	20.1	20.6	21.2	22.6	15.2	15.7	16.2	16.8	18.2
	12H	21.4	21.9	22.4	22.9	24.4	16.8	17.3	17.9	18.4	19.9
8H 4H	4H	15.4	15.9	16.4	17.0	18.5	12.5	13.1	13.6	14.1	15.6
	6H	18.7	19.2	19.8	20.3	21.7	15.5	15.9	16.5	17.0	18.5
	8H	20.6	21.0	21.6	22.1	23.5	17.1	17.5	18.2	18.6	20.1
	12H	22.6	23.0	23.7	24.1	25.6	18.9	19.3	20.0	20.4	21.9
12H 4H	4H	15.5	16.0	16.6	17.1	18.6	13.2	13.7	14.3	14.8	16.2
	6H	19.0	19.4	20.0	20.5	21.9	16.2	16.6	17.3	17.7	19.2
	8H	20.9	21.3	22.0	22.4	23.8	18.0	18.4	19.1	19.5	20.9
Variation of the observer position for the luminaire distance S											
S = 1.0H	+0.2 / -0.2					+0.2 / -0.2					
S = 1.5H	+0.3 / -0.4					+0.3 / -0.4					
S = 2.0H	+0.5 / -0.6					+0.5 / -0.6					
Standard table	---					---					
Correction summand	---					---					
Corrected glare indices referring to 373 lm total luminous flux											

COEFFICIENTS OF UTILIZATION

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
<b>RCR</b>	<b>(RCR: Room Cavity Ratio)</b>																	
	Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	105	105	105	105	96	96	96	96	79	79	79	63	63	63	49	49	49	42
1	90	83	76	71	81	75	69	64	60	55	52	46	43	40	33	31	28	22
2	79	69	61	53	71	62	55	48	49	43	38	37	33	29	26	23	20	14
3	71	59	50	42	64	53	45	38	42	35	30	31	26	22	21	18	15	10
4	64	51	42	34	58	46	37	31	36	29	24	27	22	18	18	15	11	7
5	59	45	35	28	52	40	32	26	32	25	20	24	19	15	16	12	9	6
6	54	40	31	24	48	36	28	22	28	22	17	21	16	12	14	11	8	4
7	50	36	27	20	44	32	24	18	25	19	14	19	14	10	13	9	6	3
8	46	32	24	18	41	29	21	16	23	17	12	17	12	9	12	8	6	3
9	42	29	21	15	38	26	19	14	21	15	11	16	11	8	11	7	5	2
10	40	27	19	14	36	24	17	12	19	13	9	14	10	7	10	7	4	2



ZONAL LUMEN SUMMARY

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
0.433 lm	1.69 lm	3.83 lm	7.04 lm	11.7 lm	18.5 lm	27.3 lm	37.3 lm	48.4 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
52.0 lm	49.3 lm	42.9 lm	31.9 lm	19.6 lm	11.3 lm	6.20 lm	2.93 lm	0.774 lm




FLICKER


FLICKER CURVE (COMPLETE SAMPLED FLICKER)



FLICKER FRAME (FRAME OF ONE FLICKER PERIOD)



FLICKER FFT (FREQUENCY SCOPE OF FLICKER CURVE)



FLICKER RESULTS:

Flicker frequency:	99.75 Hz
Flicker index:	0
Flicker percentage:	1.04 %
SVM: (Visual flicker)	0.04

FLICKER CONDITIONS:

Sample rate:	40000 samples/second
--------------	----------------------