

INDOOR


SOSPENSIONE / SUSPENSION

OVERFLY




- alluminio, metacrilato
- colore cavo: nero
- con cavo 5m: + 53€

- aluminum, methacrylate
- cable color: black
- with 5-meters cable: + 53€



Con rosone e driver / With canopy and driver


	M 2700K	W 3000K	N 4000K
3423			
Potenza/ Power	1x19.0W	1x19.0W	1x19.0W
Nominal lumen	1x2616lm	1x3050lm	1x3200lm
CRI	>90	>90	>90
Alimentazione/ Supply	220-240V	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Disco Disk	Stelo Stem
3423	M	-BO	-BO	-BO
composed by	W	-NO	-NO	-NO
RS04/03 (1Pz)	N	-BV	-BV	-BV
3426 (1Pz)		-OR	-OR	-OR
		-TI	-TI	-TI
		-RR	-RR	-RR

Con rosone e driver / With canopy and driver

	M 2700K	W 3000K	N 4000K
3424			
Potenza/ Power	1x19.0W	1x19.0W	1x19.0W
Nominal lumen	1x2616lm	1x3050lm	1x3200lm
CRI	>90	>90	>90
Alimentazione/ Supply	220-240V	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Disco Disk	Stelo Stem
3424	M	-BO	-BO	-BO
composed by	W	-NO	-NO	-NO
RS04/02 (1Pz)	N	-BV	-BV	-BV
3426 (1Pz)		-OR	-OR	-OR
		-TI	-TI	-TI
		-RR	-RR	-RR




Con rosone, senza driver / With canopy, without driver


	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x19.0W	1x19.0W	1x19.0W
Nominal lumen	1x2616lm	1x3050lm	1x3200lm
CRI	>90	>90	>90
Alimentazione/ Supply	500mA	500mA	500mA



Articolo Item	Temperatura Temperature	Rosone Canopy	Disco Disk	Stelo Stem
3421	M	-BO	-BO	-BO
..... composed by	W	-NO	-NO	-NO
RS01 (1Pz)	N	-BV	-BV	-BV
3426 (1Pz)		-OR	-OR	-OR
		-TI	-TI	-TI
		-RR	-RR	-RR

Con rosone per incasso, senza driver / With canopy for built-in application, without driver



	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x19.0W	1x19.0W	1x19.0W
Nominal lumen	1x2616lm	1x3050lm	1x3200lm
CRI	>90	>90	>90
Alimentazione/ Supply	500mA	500mA	500mA



Articolo Item	Temperatura Temperature	Rosone Canopy	Disco Disk	Stelo Stem
3422	M	-BO	-BO	-BO
..... composed by	W	-NO	-NO	-NO
RS06 (1Pz)	N	-BV	-BV	-BV
3426 (1Pz)		-OR	-OR	-OR
		-TI	-TI	-TI
		-RR	-RR	-RR

Solo corpo / Body only


	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x19.0W	1x19.0W	1x19.0W
Nominal lumen	1x2616lm	1x3050lm	1x3200lm
CRI	>90	>90	>90
Alimentazione/ Supply	500mA	500mA	500mA




Articolo Item	Temperatura Temperature	Disco Disk	Stelo Stem
3426	M	-BO	-BO
	W	-NO	-NO
	N	-BV	-BV
		-OR	-OR
		-TI	-TI
		-RR	-RR

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver



Solo corpo con cavo 5m / Body only with 5m cable

	M 2700K	W 3000K	N 4000K
Potenza/ Power	1x19.0W	1x19.0W	1x19.0W
Nominal lumen	1x2616lm	1x3050lm	1x3200lm
CRI	>90	>90	>90
Alimentazione/ Supply	500mA	500mA	500mA




Articolo Item	Temperatura Temperature	Disco Disk	Stelo Stem
3426/05	M	-BO	-BO
	W	-NO	-NO
	N	-BV	-BV
		-OR	-OR
		-TI	-TI
		-RR	-RR

Necessita di driver remoto a 500mA oppure di convertitore da 48Vdc a 500mA più driver a 48Vdc
Requires 500mA remote driver, or 48Vdc to 500 mA converter and 48Vdc driver

Driver in corrente in remoto / Remote constant current drivers

Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
2A9535	1	20W	IP20	78x40,5x22	PUSH DALI

Convertitore da 48Vdc a 500mA / 48Vdc to 500 mA converter



Articolo Item	art. alimentabili items powerable
2A7900	1

Necessita di driver remoto a 48Vdc
Requires 48V remote driver

Driver 48Vdc in tensione in remoto / Remote constant voltage drivers 48Vdc






















Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0633	1-2	70W	IP20	210x45x49	ON-OFF
1A0634	1-4	150W	IP20	210x45x49	ON-OFF
1A1239	1-6	240W	IP67	244x68x39	ON-OFF
1A2493	1-8	320W	IP67	252x90x44	ON-OFF

Centraline dimmerabili in remoto / Remote dimmable controllers




Articolo Item	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0837/48	288W	IP20	132x22x20	PUSH DALI 1-10V
1A0838/48	576W	IP20	164x38x25	PUSH DALI 0-10V 1-10V
1A0172/48	576W	IP20	57x44x25	PUSH CASAMBI

Controller 1 canale - DC
1-channel controller - DC

Rosoni rotondi con driver / Round canopies with driver


	Articolo Item	Finitura Finish	Dimmerazione Dimming
3 Sospensioni 3 suspensions	RS88/02	-BI  -NE  -BV 	ON-OFF PUSH DALI 0-10V
			
3 Sospensioni 3 suspensions	RS88/03	-BI  -NE  -BV 	ON-OFF PUSH CASAMBI
4 Sospensioni 4 suspensions	RS88/05	-BI  -NE  -BV 	ON-OFF PUSH DALI 0-10V
			
4 Sospensioni 4 suspensions	RS88/06	-BI  -NE  -BV 	ON-OFF PUSH CASAMBI
6 Sospensioni 6 suspensions	RS88/08	-BI  -NE  -BV 	ON-OFF PUSH DALI 0-10V
			
6 Sospensioni 6 suspensions	RS88/09	-BI  -NE  -BV 	ON-OFF PUSH CASAMBI

Rosoni rettangolari con driver / Square canopies with driver

	Articolo Item	Finitura Finish	Dimmerazione Dimming
3 Sospensioni 3 suspensions	RS58/01	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
3 Sospensioni 3 suspensions	RS58/02	-BI -NE -BV	ON-OFF PUSH CASAMBI
4 Sospensioni 4 suspensions	RS58/11	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
4 Sospensioni 4 suspensions	RS58/12	-BI -NE -BV	ON-OFF PUSH CASAMBI
6 Sospensioni 6 suspensions	RS58/21	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
6 Sospensioni 6 suspensions	RS58/22	-BI -NE -BV	ON-OFF PUSH CASAMBI

Rosone con driver + staffa Batacù per decentramento 1pz

Canopy with driver + Batacù bracket for decentralization 1pc




Articolo Item	Finitura Finish	Dimmerazione Dimming
521	-NE 	PUSH DALI
composed by		
RS69 (1Pz)		
520 (1Pz)		

Necessita di lampada versione "Solo corpo con cavo 5m"
Requires "Body only with 5m cable" lamp version


Rosone con driver + staffa Batacù per decentramento 3pz

Canopy with driver + Batacù bracket for decentralization 3pcs




Articolo Item	Finitura Finish	Dimmerazione Dimming
523	-NE 	PUSH DALI
composed by		
RS92 (1Pz)		
520 (3Pz)		


Necessita di lampada versione "Solo corpo con cavo 5m"
Requires "Body only with 5m cable" lamp version

Jack per track 48V + Connettore nero / Jack for track 48V + black connector

Articolo Item	Finitura Finish	Dimmerazione Dimming
201/01	-JBI 	ON-OFF
	-JNE 	



201/02	-JBI 	0-10V
	-JNE 	



201/03	-JBI 	DALI
	-JNE 	

Jack per track 230V + Connettore nero / Jack for track 230V + black connector

	Articolo Item	Finitura Finish	Dimmerazione Dimming ON-OFF
	211/02	-JBI -JNE	ON-OFF
	211/05	-JBI -JNE	L-C
	211/06	-JBI -JNE	DALI
	211/09	-JBI -JNE	CASAMBI

Passacavi / Cable entry

	Articolo Item	Finitura Finish
	BEAMKIT01	-NA
	BEAMKIT02	-NA