



# MUSE DOUBLE LIGHT acoustic suspended

091-122163BF

PROJECT

TYPE

NOTES

QUANTITY

DATE

## GENERAL

Ceiling

Suspended

anthracite

3670 lm/m

IP20

4400 lm

## LED

4000 K

CRI  $\geq 80$

L90 / 50000 h

initial  $\leq 3$  MacAdam

## OPTICAL

UGR  $< 19$

$\geq 65^\circ < 1500$  cd/m<sup>2</sup>

## PHYSICAL

Cable 1500 mm

length 1600 mm

width 646 mm

height 700 mm

9.5 kg

## ELECTRICAL

DALI-2

41 W

107 lm/W

1 DALI Addr.

PC1 220-240V

34 W/m



Luminaire body made of high-quality, self-supporting polyester fleece with sound absorbing properties, consisting of 50% recycled PET; high-quality visual and tactile surface, anthracite; colour may deviate; constructed of 2 shells to form cavities that improve acoustic performance; large sound absorbing surface; suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; incl. transparent feed; optimised for the illumination of 2 office workstations opposite each other; light inset made from extruded profile for improved thermal management; light colour 4000 K; Binning initial  $\leq 3$  MacAdam; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high-quality, chromed reflector with faceted design; blind covers in gray; UGR  $\leq 19$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500$  cd/m<sup>2</sup>; degree of protection IP20; PC1 220-240V; internal wiring in light halogen free; incl. DALI-2 converter;

## Light Distribution

