

PRODUCT DATASHEET

LED WORKLIGHT VALUE BATTERY PANEL

26W 865

WORKLIGHTS VALUE BATTERY | Mobile battery powered worklight in value class



Areas of application

- Renovation
- Garages
- Workshops
- Basement

Product benefits

- USB-Charging function from integrated power bank feature
- Independent of power supply due to battery technology

Product features

- Worklight with swiveling head
- Battery powered, portable worklight
- Battery rechargeable via USB cable



TECHNICAL DATA

Electrical data

Nominal wattage	26.00 W
Nominal voltage	13 V
Nominal current	800.000 mA
Power factor λ	1.00
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	3000 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥ 80
Standard deviation of color matching	< 6 sdc _m
Photobiological safety group acc. to EN62778	RG1
Beam angle	108 °

Dimensions & Weight

Length	385.00 mm
Width	70.00 mm
Height	315.00 mm
Product weight	2000.00 g
Cable length	600 mm



LED WORKLIGHT VAL BAT PANEL
30W 865

Materials & Colors

Product color	Black/Gray
---------------	------------

Housing color	Black/Gray
Body material	Plastic
Cover material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+40 °C
Temperature range at storage	-20...+60 °C
Type of connection	Plug type C (EU)
Type of protection	IP54
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	2DIM
Mounting type	Standing
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	15000 h ¹⁾
Number of switching cycles	7500

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Battery size [GMS]	Others
Battery charging time	8 h

Certificates & Standards

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– 60cm USB-C charging cable

Safety advice

– To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's

reach.

- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED WORKLIGHT VAL BAT PANEL
	Legal information	Safety insert G11219286
	Declarations of conformity	LED WORKLIGHT VAL BAT PANEL

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854430497	Folding box 1	75 mm x 390 mm x 325 mm	2412.00 g	9.51 dm ³
4099854430503	Shipping box 5	405 mm x 400 mm x 350 mm	12060.00 g	56.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.