

754-789-16 MICROPERFETTO 26W 30K 30° PWM NE

Code: 754-789-16

Low-voltage 48V electrified track spotlight designed for high-efficiency COB LEDs. It is equipped with reflector.



General specifications

Designer	Ivela Design Team
Commercial brand	Microperfetto
Installation environment	Interior
Native mounting type	Track mounted
Mounting type	Track attachment
Ideal application locations	Residential, Hospitality, Showroom, Museum, Office, Commercial space
Wire incandescent test	850
Made in	Italy

Physical specifications

Shape	Cylindrical
Body material	Aluminum
Body finish	Matte
Body color	Black
Frontal material	Aluminum
Frontal finish	Matte
Thermal dissipation	Passive
IP	IP20

Lighting specifications

N° of light sources	1
Lumen	1890
L.O.R. (%)	70

Ivela Srl

Via B. Buozzi 15 - 20050 Liscate (Milano)
Tel. +39 02 9500121 - info@ivela.it - www.ivela.it

Power	26
Light type	White
CCT	3000K
CRI	90
SDCM	3
RG	RG1
Life time	L80B10
LB value @ h	50000

Optical specifications

Emission type	Direct monoemission
Beam	30
Optics type	Mirror metallized thermoplastic reflector
Optical diffuser finish	Metallized
Optical diffuser material	Termoplastic
Orientability	Adjustable
Rotation degrees	355
Swivel degrees (°)	90

Electrical specifications

Power supply availability	Not included
Power supply position	Internal
CV / CC converter availability	Included
CV / CC converter position	Internal
Dimmable	Yes
Dimmer availability	Not included
Dimming type	ON/OFF
Dimmer position	Remote
Power supply voltage type	DC
Power supply type	Voltage
Input Voltage (V)	48
Insulation class	III
Light source type	LED COB
Energy efficiency class	E
Replaceable power supply system	Replaceable by skilled personnel
Replaceable light source	Replaceable by skilled personnel

Dimensions and weight

Length (mm)	210
-------------	-----

Diameter (mm)	53
---------------	----

General conditions

Warranty	5 years
----------	---------
