

# PRODUCT DATASHEET SMART+ Wifi Undercabinet Slim 50x3.75 TW EXT

SMART+ UNDERCABINET SLIM TUNABLE WHITE | Slim Undercabinet luminaire with WIFI technology



## Areas of application

- Indoor applications
- Shelf and undercabinet lighting
- Kitchens, workspaces
- Shelves

#### Product benefits

- Wireless control via app or voice control
- Very slim design
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

#### **Product features**

- Variety of combinations possible
- Provides functional or mood lighting
- $\,$  Adjustable color temperature via Tunable White: 2,700...6,500 K
- Dimmable
- Available in different sizes: 50x3.75 cm, 45.7x6.5 cm, 60x6.5 cm
- 50 cm luminaire extendable with maximum two extensions of 50 cm each
- Controllable via voice control available: Google Assistant or Amazon Alexa



- Network protocol: WiFi
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)

TW EXT

# TECHNICAL DATA

# Electrical data

Nominal wattage	8.00 W
Nominal voltage	24 V
Mains frequency	5060 Hz
Nominal current	330.000 mA
Power factor $\lambda$	≥0.5
Protection class	III
Operating mode	Integrated LED driver

#### Photometrical data

Luminous flux	480 lm
Luminous efficacy	60 lm/W
Color temperature	27006500 K
Light color (designation)	Tunable White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	120°

# Dimensions & Weight

Length	500.00 mm
Width	38.00 mm
Height	8.00 mm
Product weight	230.00 g

# SMART WIFI UNDERCABINET

#### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Plastic

Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

#### **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Application environment	Indoor
With light source	Yes

#### Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

#### Certificates & Standards

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

## **EQUIPMENT / ACCESSORIES**

- Control via app or voice control requires compatible Smart home system
- Power supply (2 m) and control box (5 cm) is included with basic version
- Extensions available in lengths: 30 cm and 50 cm
- Extensions are supplied with a connector and a connector cable (10 cm)
- Power supply and control box are not included with extensions
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

#### Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

#### **DOWNLOAD DATA**

TW EXT

	Documents and certificates	Document name	
POF	User instruction / safety instructions	SMART+ WIFI UNDERCABINET	
PDF	Legal information	Safety insert G11226267	
PDF	Declarations of conformity	SMART WIFI UNDERCABINET	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854530517	Folding box 1	50 mm x 82 mm x 510 mm	319.00 g	2.09 dm <sup>3</sup>
4099854530524	Shipping box 8	560 mm x 210 mm x 185 mm	3227.00 g	21.76 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

TW EXT