

PRODUCT NO. 3026-160120

DOTLUX LED-Akkustrahler WORKER 30W 6500K 7,4V



to the product page

- Adjustable, glare-free light surfaces for homogeneous illumination with snap-in function
- Extremely compact, impact-resistant (IK08) and splash-proof (IP65) plastic housing
- Ergonomic carrying handle with integrated metal tripod mount
- Dimmable in three brightness levels
 - 30% light output = 7.0 Hours
 - 50% light output = 4.5 Hours
 - 100% light output = 2.2 Hours
 - (charging time max. 3.8 hours)
- Incl. charging cable for car/truck 12/24V and 220 V
- Inexpensive, replaceable, integrated lithium-ion rechargeable battery
- Continuous operation possible via 220 V charging cable at full brightness level

WEIGHT IN KG	2.1
POWER CONSUMPTION IN WATTS	30
CONSUMPTION (KWH/1000H)	30
NET LUMINOUS FLUX IN LUMENS	2900
LUMEN PER WATT	97

Dimensions

length: 400mm
width: 210mm
height: 100mm

BEAM ANGLE	120°
DIMMABLE	Step dimming
ENABLED LICENSED PRODUCT	Yes
INPUT VOLTAGE	220-240 V AC
ENERGY EFFICIENCY 2019/2015	F
COLOR TEMPERATURE IN KELVIN	6500
COLOR-RENDERING-INDEX	CRI > 80
WARRANTY	3 years
IK PROTECTION	IK07
L/B VALUE	L80/B10
LIFETIME	approx. 40.000 h at 25°C
LIGHT COLOR	daylight white
COVER MATERIAL	Polycarbonate PC
HOUSING MATERIAL	Impact-resistant plastic
SWITCH CYCLES	> 80.000
IP-PROTECION	IP65
ASSORTMENT	Proline
TEMPERATURE RANGE	-10°C to +40°C