



## Info generali

### Interno - Lampade da parete

Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission

|                      |                         |
|----------------------|-------------------------|
| <b>Ean</b>           | 8021696307466           |
| <b>Articolo</b>      | KID MAP2 NERO           |
| <b>Installazione</b> | Lampade da parete       |
| <b>Garanzia</b>      | 5 years                 |
| <b>Peso lordo</b>    | 0.44 kg                 |
| <b>Volume</b>        | 0.001658 m <sup>3</sup> |

## Info tecniche e installative

|                                  |  |
|----------------------------------|--|
| <b>Peso netto</b>                | 0.35 kg  |
| <b>Classe di isolamento</b>      | II   |
| <b>Grado di protezione</b>       | IP20   |
| <b>Conformità</b>                | CE   |
| <b>Temperatura d'esercizio</b>   | 0° ~ +40 °C  |
| <b>Efficienza a pieno carico</b> | x  |
| <b>Dimmer</b>                    | NO, On-Off   |
| <b>Alimentazione</b>             | 220-240 V AC 50/60 Hz<br>Integrated switch button                              |
| <b>Alimentatore</b>              | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| <b>Accessori non inclusi</b>     | Decorative diffuser  |

## Info sorgente e prestazionali

|                              |  |
|------------------------------|--|
| <b>Sorgente integrata</b>    | Light bulb (included), Integrated LED module |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only)    |
| <b>Potenza</b>               | 3 W  |
| <b>Emissione</b>             | Diffuse + Direct                             |
| <b>Consumo massimo</b>       | max 3,00 W                                   |
| <b>Caratteristiche LED</b>   | -  |
| <b>CCT LED</b>               | 3000 K                                       |
| <b>Durata LED (t. 25°c)</b>  | -  |
| <b>CRI</b>                   | > 90   |
| <b>Fascio luminoso</b>       | 23°  |
| <b>Flusso sorgente</b>       | 160 lm                                       |
| <b>Flusso utile</b>          | 140 lm                                       |
| <b>Rischio fotobiologico</b> | 2  |