

## PRODUCT DATASHEET

# Battery LED Spotlight Sensor 10W 4000K IP54 Black

Battery LED Spotlight Double | Outdoor spotlights with double luminaire head

---

### Areas of application

- Outdoor
- Areas where no power supply is available



---

### Product benefits

- Demand based lighting and energy saving thanks to motion and daylight sensor
- Independent of power supply due to battery technology
- Energy-efficient thanks to LED technology

---

### Product features

- Luminous flux: up to 480 lm
- Integrated light and motion sensor
- Battery life in continuous operation: up to 5 h
- Type of protection: IP54



TECHNICAL DATA

Electrical data


Nominal wattage	10.00 W
Nominal voltage	6 V
Mains frequency	0 Hz
Nominal current	2000.000 mA
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	480 lm
Luminous efficacy	48 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Beam angle	95 °

Dimensions & Weight

Length	332.00 mm
Width	105.00 mm
Height	112.00 mm
Product weight	390.00 g



BATTERY LED SPOTLIGHT  
DOUBLE BK OSRAM

Materials & Colors

Product color	Black
Housing color	Black
Body material	Acrylonitrile butadiene styrene (ABS)
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	-20...+30 °C
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	15000 h <sup>1)</sup>
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Sensor

Type of sensor	Motion / Light
----------------	----------------

## BATTERY

Type of Battery	Alkaline
Nominal voltage of battery	1.5 V

## Certificates & Standards

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable



## EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

## Safety advice

- This product is not a toy. It should not be left unattended in the hands of children or operated by children.
- Not designed as a replacement for conventional lighting in private household.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

## DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	BATTERY LED SPOTLIGHT
 Declarations of conformity	CE declaration Battery Spotlights

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854497551	Folding box 1	127 mm x 142 mm x 200 mm	615.00 g	3.61 dm <sup>3</sup>
4099854497568	Shipping box 4	302 mm x 272 mm x 227 mm	2460.00 g	18.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.