

by Philippe Starck , 2006

Floor lamp providing diffused lighting. Base, rod support and diffuser support in die-cast, polished and chrome-plated Zamak alloy. Galvanized P04 steel base cover. Injectionmolded PC (polycarbonate) opal inner diffuser and support for the lamp-holder. Outer diffusers in transparent or fumèe PMMA (polymethylmethacrylate), and silver or bronze on the inner surface, by vacuum aluminum coating. Injectionmolded PC (polycarbonate) upper ring, completely transparent or transparent diffuser and silver diffuser) or transparent brown for the outer bronze diffuser. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Mounting Environment Weight Light sources available	Floor Indoor 6.7 Kg 1 x RF26998 LED 21W E27 24521m 3000K CRI80 [e] Dimmable
Emergency Switching	Without On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Dimmer Voltage Power Battery Supply included	Included 220-240V MAX 150W No Yes
Cord Length Materials	2010 mm Aluminum, Fabric, Polycarbonate, Polymethylmethacrylate
Colors	<ul> <li>F6305007 - Fabric</li> <li>F6305000 - Transparent</li> <li>F6305004 - Aluminized Silver</li> <li>F6305046 - Aluminized Bronze</li> <li>F6305030 - Fumée</li> </ul>
Certificate	





