

XAL NOD suspended

072-65225180

GENERAL

Ceiling
Suspended
black matt
IP20
1040 lm

LED

3000 K
CRI \geq 90
L85 / 50000 h
photobio. safety RG 0 - no Risk
initial \leq 3 MacAdam

OPTICAL

Opal

PHYSICAL

Rod 1500 mm
diameter 250 mm
height 125 mm
0.55 kg
tilt max 180°
rotation 330°

ELECTRICAL

non DIM / phase-cut
9.8 W
106 lm/W
PC1 220-240V

PROJECT

TYPE

NOTES

QUANTITY



DATE



Product family description

Cone-shaped luminaire housing made of plastic; luminaire housing 330° rotatable and 180° tiltable pivot-mounted; elegant suspended luminaire with black soft-touch surface; with adjustable pendant rod mounting 1500mm or 2500mm; feed in rod; completely homogeneously illuminated, satinised PMMA cover; energy-efficient LEDs with very good colour rendering; binning initial \leq 3 MacAdam; available in the light colours 2700K and 3000K; CRI \geq 90; min. 85% of the luminous flux after 50000 hours; degree of protection IP 20; PC I; photobiological safety according to IEC 62471 risk group 0; incl. converter, non dimmable

Light Distribution



XAL NOD suspended

072-65225180

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	50
B13	65
B16	80
B20	100
C10	50
C13	65
C16	80
C20	100

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.92	0.9	0.87
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.