


**CELTIS MINI LED surface mounted luminaire 330 mm, with indirect light component**

Article no. 58212003

Light.  
For Generations.**Tender**

LED surface mounted luminaire 330 mm, with indirect light component, Round. Luminaire diameter 330.0 mm, Height 70.0 mm Weight 2.337 kg, with rotationssymmetrical, deep, wide distributed light intensity. Shade material: Chintz, Shade colour: Dark brown gray Luminous flux 1.360 lm, Power 1 x 15 W, System Efficiency 91 lm/W, Light colour warm white, Correlated color temperature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Steel, Colour: White, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. on/off switchable.

Article data	
Article no.	58212003
GTIN	4251433920991
Series name	CELTIS MINI
Short description	LED surface mounted luminaire 330 mm, with indirect light component
Material	Steel
Colour	White
Shape	Round
Outer diameter	330 mm
Height	70 mm
Shade colour	Dark brown gray
Shade material	Chintz
Chintz colour code	66.8003.83
Weight	2.337 kg

**CELTIS MINI LED surface mounted luminaire 330 mm, with indirect light component**

Article no. 58212003

Light.  
For Generations.

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Luminous flux	1,360 lm
System efficiency	91 lm/W
Colour rendering	CRI > 80
Reflector	Without
Light sharing	Symmetric

Operating technology of the luminaire	
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable

Packing data	
Gross weight	4.255 kg
Length of packaging	400 mm
Packaging width	400 mm
Packaging height	315 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.