




White ceiling fan with SMD LED 15W 3000K. It has round and modern lines ideal for the ventilation of areas ranging from 13m2 to 17m2. This ceiling fan has DC motor. Operated on remote control (included). It offers 5 adjustable speeds with a consumption of 3 - 5 - 9 - 14 - 24W and 93 - 128 - 166 - 192 - 233W revolutions per minute depending on speed. This fan comes with reverse function, so you can also use it in winter, improving the efficiency of your heating system. Airflow: 180,57 m3 min / 6377 CFM. This ceiling fan is suitable for inclining roof.



**Energy level** 

## **General characteristics**

Туре	II
IP	20
voltage	220V-240V
Hertz	50/60Hz
Power	24W
W	3,9-5,8-9,5-14-24
RPM	93-128-166-192-233
Airflow (m3/min)	247
Reverse function	Si
Engine type	DC
No. of blades	3
Pitched ceiling	No
Can be installed without seat	No
post	
Type of control included	Remote control with

timer

## Material

Body/StructureSteelDiffuserPPBlade materialPlywood

## **Lighting characteristics**

Light source included	
Light source	SMD LED
Temperature	6000K
Adjustable colour temperature	Yes
MacAdam Steps	>5 SDCM
CRI	>80
LED lifetime	50000H
Light direction	Ambient lighting
Energy classification	G
Driver	
D. Saran and A. J. J.	01
Driver embedded	SI
File download	
General documents	Download >
2D / 3D	Download >

Download >

## **Finish**

Body/Structure Matt White Diffuser Opal White

