

PRODUCT NO. 4558-030360

**DOTLUX LED bollard light WAY 20cm 7,5/15W 3000K**



to the product page

Dotlux LED bollard light WAY 20 cm

- Free choice of light emission surface due to interchangeable glass and cover plates
- Power-Select allows adjustment of system power 50% / 100%
- High-quality aluminium housing with powder coating in DB703
- Rugged, splash-proof design for outdoor use with IP 54 protection
- Glare-free and homogeneous light distribution with high colour rendering Ra>82
- EasyMount platform enables quick and easy installation
- For loop-through with connection box (input and output each for 3 x 4 mm<sup>2</sup> cable)
- Mounting base made of special aluminium alloy, approved for installation with earth contact

<b>WEIGHT IN KG</b>	1.5	<b>BEAM ANGLE</b>	360°
<b>POWER CONSUMPTION IN WATTS</b>	7,5-15	<b>ENABLED LICENSED PRODUCT</b>	Yes
<b>NET LUMINOUS FLUX IN LUMENS</b>	400/800	<b>INPUT VOLTAGE</b>	176-240V AC/DC
<b>LUMEN PER WATT</b>	53	<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>WARRANTY</b>	5 years
		<b>HOUSING COLOUR</b>	gray
<b>Dimensions</b>		<b>IK PROTECTION</b>	IK06
<b>length:</b> 120mm		<b>L/B VALUE</b>	L80/B10
<b>width:</b> 120mm		<b>LIFETIME</b>	approx. 40.000 h at 25°C
<b>height:</b> 200mm		<b>MATERIAL</b>	Aluminium
		<b>IP-PROTECION</b>	IP65
		<b>ASSORTMENT</b>	Proline
		<b>TEMPERATURE RANGE</b>	-25°C to +45°C