

INDOOR



SOSPENSIONE / SUSPENSION

BEAM STICK NUANCE Ø200 + "Balloton Edition"




- alluminio, vetro soffiato a bocca
- colore cavo: nero
- con cavo 5m: + 53€

- aluminum, mouthblown glass
- cable color: black
- with 5-meters cable: + 53€




Con rosone e driver / With canopy and driver

4692	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
4692	M	-BO	-BO	-VBI
..... composed by	W	-NO	-NO	-VBL
RS03/02 (1Pz)		-BV	-BV	-VTM
4682 (1Pz)		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BAM
				-BTM
				-BVF



Con rosone e driver / With canopy and driver

4694	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
4694 composed by RS03/04 (1Pz) 4682 (1Pz)	M	-BO	-BO	-VBI
	W	-NO	-NO	-VBL
		-BV	-BV	-VTM
		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BAM
				-BTM
				-BVF



Con rosone e driver / With canopy and driver

4693	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	220-240V	220-240V




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
4693 composed by RS03/03 (1Pz) 4682 (1Pz)	M	-BO	-BO	-VBI
	W	-NO	-NO	-VBL
		-BV	-BV	-VTM
		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BAM
				-BTM
				-BVF



Con rosone, senza driver / With canopy, without driver

4690	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	500mA	500mA




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
4690	M	-BO	-BO	-VBI
... composed by	W	-NO	-NO	-VBL
RS01 (1Pz)		-BV	-BV	-VTM
4682 (1Pz)		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BAM
				-BTM
				-BVF

Con rosone per incasso, senza driver / With canopy for built-in application, without driver



4691	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	500mA	500mA




Articolo Item	Temperatura Temperature	Rosone Canopy	Corpo Body	Vetro Glass
4691	M	-BO	-BO	-VBI
... composed by	W	-NO	-NO	-VBL
RS06 (1Pz)		-BV	-BV	-VTM
4682 (1Pz)		-OR	-OR	-VAM
		-RR	-RR	-VRS
		-TI	-TI	-VFU
		-VF	-VF	-VVF
				-BAM
				-BTM
				-BVF



Solo corpo / Body only

4682	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	500mA	500mA




Articolo Item	Temperatura Temperature	Corpo Body	Vetro Glass
4682	M	-BO	-VBI
	W	-NO	-VBL
		-BV	-VTM
		-OR	-VAM
		-RR	-VRS
		-TI	-VFU
		-VF	-VVF
			-BAM
			-BTM
			-BVF

Necessita di driver remoto a 500mA oppure di convertitore da 24Vdc a 500mA più driver a 24Vdc
Requires 500mA remote driver, or 24Vdc to 500 mA converter and 24Vdc driver



Solo corpo con cavo 5m / Body only with 5m cable

4682/01	M 2700K	W 3000K
Potenza/ Power	2x4.3W	2x4.3W
Nominal lumen	2x492lm	2x523lm
CRI	>90	>90
Alimentazione/ Supply	500mA	500mA




Articolo Item	Temperatura Temperature	Corpo Body	Vetro Glass
4682/01	M	-BO	-VBI
	W	-NO	-VBL
		-BV	-VTM
		-OR	-VAM
		-RR	-VRS
		-TI	-VFU
		-VF	-VVF
			-BAM
			-BTM
			-BVF

Necessita di driver remoto a 500mA oppure di convertitore da 24Vdc a 500mA più driver a 24Vdc
Requires 500mA remote driver, or 24Vdc to 500 mA converter and 24Vdc driver

Driver in corrente in remoto / Remote constant current drivers

Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A2399	1	10W	IP20	102x38x21	L-C

Convertitore da 24Vdc a 500mA / 24Vdc to 500 mA converter

Necessita di driver remoto a 24Vdc
Requires 24V remote driver

Articolo Item	art. alimentabili items powerable
2A4843	1

Driver 24Vdc in tensione in remoto / Remote constant voltage drivers 24Vdc




Articolo Item	art. alimentabili items powerable	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0530	1	8W	IP20	42x40x22	ON-OFF
1A0150	1-2	30W	IP20	154x50x14	ON-OFF
1A1910	1-4	60W	IP20	185x63,5x22	ON-OFF
1A1476	1-7	100W	IP20	177x56,4x17,2	ON-OFF
1A2168	1-7	100W	IP20	190x65x22	PUSH DALI
1A1999	1-7	100W	IP20	201x63x30	L-C

Centraline dimmerabili in remoto / Remote dimmable controllers

Articolo Item	Potenza Power	IP	Dimensioni Dimensions	Dimmerazione Dimming
1A0837/24	144W	IP20	132x22x20	PUSH DALI 1-10V
1A0838/24	288W	IP20	164x38x25	PUSH DALI 0-10V 1-10V
1A0172/24	288W	IP20	57x44x25	PUSH CASAMBI


Controller 1 canale - DC
1-channel controller - DC

Rosoni rotondi con driver / Round canopies with driver


	Articolo Item	Finitura Finish	Dimmerazione Dimming
3 Sospensioni 3 suspensions	RS88/02	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
3 Sospensioni 3 suspensions	RS88/03	-BI -NE -BV	ON-OFF PUSH CASAMBI
3 Sospensioni 3 suspensions	RS88/01	-BI -NE -BV	L-C ON-OFF
4 Sospensioni 4 suspensions	RS88/05	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
4 Sospensioni 4 suspensions	RS88/06	-BI -NE -BV	ON-OFF PUSH CASAMBI
4 Sospensioni 4 suspensions	RS88/04	-BI -NE -BV	L-C ON-OFF
6 Sospensioni 6 suspensions	RS88/08	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
6 Sospensioni 6 suspensions	RS88/09	-BI -NE -BV	ON-OFF PUSH CASAMBI
6 Sospensioni 6 suspensions	RS88/07	-BI -NE -BV	L-C ON-OFF

9 Sospensioni
9 suspensions

RS89/02




-BI 
-NE 
-BV 

ON-OFF | PUSH | DALI | 0-10V |



9 Sospensioni
9 suspensions

RS89/03

-BI 
-NE 
-BV 

ON-OFF | PUSH | CASAMBI

9 Sospensioni
9 suspensions

RS89/01

-BI 
-NE 
-BV 


L-C | ON-OFF

10 Sospensioni
10 suspensions

RS89/05




-BI 
-NE 
-BV 

ON-OFF | PUSH | DALI | 0-10V |



10 Sospensioni
10 suspensions

RS89/06

-BI 
-NE 
-BV 

ON-OFF | PUSH | CASAMBI




10 Sospensioni
10 suspensions

RS89/04

-BI 
-NE 
-BV 


L-C | ON-OFF

Rosoni rettangolari con driver / Square canopies with driver

	Articolo Item	Finitura Finish	Dimmerazione Dimming
3 Sospensioni 3 suspensions	RS58/01	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
3 Sospensioni 3 suspensions	RS58/02	-BI -NE -BV	ON-OFF PUSH CASAMBI
3 Sospensioni 3 suspensions	RS58/03	-BI -NE -BV	L-C ON-OFF
4 Sospensioni 4 suspensions	RS58/11	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
4 Sospensioni 4 suspensions	RS58/12	-BI -NE -BV	ON-OFF PUSH CASAMBI
4 Sospensioni 4 suspensions	RS58/13	-BI -NE -BV	L-C ON-OFF
6 Sospensioni 6 suspensions	RS58/21	-BI -NE -BV	ON-OFF PUSH DALI 0-10V
			
6 Sospensioni 6 suspensions	RS58/22	-BI -NE -BV	ON-OFF PUSH CASAMBI
6 Sospensioni 6 suspensions	RS58/23	-BI -NE -BV	L-C ON-OFF

Rosone con driver + staffa Batacù per decentramento 1pz

Canopy with driver + Batacù bracket for decentralization 1pc



Articolo

Item

521

composed by

RS69 (1Pz)

520 (1Pz)

Finitura

Finish

-NE

Dimmerazione


Dimming

PUSH | DALI

Necessita di lampada versione "Solo corpo con cavo 5m"
Requires "Body only with 5m cable" lamp version

Rosone con driver + staffa Batacù per decentramento 3pz

Canopy with driver + Batacù bracket for decentralization 3pcs



Articolo

Item

523

composed by

RS92 (1Pz)

520 (3Pz)

Finitura

Finish


-NE

Dimmerazione

Dimming

PUSH | DALI

Necessita di lampada versione "Solo corpo con cavo 5m"
Requires "Body only with 5m cable" lamp version

Jack per track 48V + Connettore nero / Jack for track 48V + black connector

Articolo

Item

201/01

Finitura


Finish

-JBI**-JNE**


Dimmerazione

Dimming

ON-OFF











**201/02****-JBI****-JNE**

0-10V




**201/03****-JBI****-JNE**

DALI

Jack per track 230V + Connettore nero / Jack for track 230V + black connector

	Articolo Item	Finitura Finish	Dimmerazione Dimming ON-OFF
	211/05	-JBI  -JNE 	L-C
	211/06	-JBI  -JNE 	DALI
	211/09	-JBI  -JNE 	CASAMBI

Passacavi / Cable entry

	Articolo Item	Finitura Finish
	BEAMKIT01	-NA 
	BEAMKIT02	-NA 