
Pad 80 With adjustable lenses - White - 9,5W 3000K - 24°

Carlotta de Bevilacqua



IP44 **⊕**



LUMINAIRE

Watt: **9.5W**Voltage: **12V**

- Delivered lumens output: 610lm

CCT: 3000KEfficiency: 73%Efficacy: 64.21lm/W

- CRI: 0

Notes

LED 9W 2x12° 3000K

DESCRIPTION

Efficient, clear accent lighting, fixed and adjustable. 3 beam angles: 2x6°, 2x12°, 2x19°. Diffused ambient lighting (in fixed version). 2 colour temperatures: warm white (3000K) and neutral white (4000K) - CRI=80 (min.). Excellent lighting efficiency > 70lm/W. High adjustability: 360° rotation, +90°/-90° tilt angle. Fixed version available as IP44. Easy installation of light modules, no tools required. Lighting units available in 3 finishes: gloss aluminium, painted white, painted black. Structural elements of recessed-mounted version available in 3 sizes, for use with 1, 2, 3 and 2x2 modules. 3 compatible finishes (polished aluminium, white, and black). Housing of ceiling-mounted version available in 3 sizes (1, 2, 3 lighting units), and 3 compatible finishes (polished aluminium, white and black). Recessed-mounted version available as trimless or framed. Materials: body in anodized extruded aluminium, diffuser in opal polycarbonate. Complies with standard EN60598-1 and other specific standards.

PRODUCT CODE: M245920

FEATURES

- Article Code: **M245920**

- Colour: White

- Series: Architectural Indoor

- Area contract: Hospitality, null, Retail, Culture

- design by: Carlotta de Bevilacqua

DIMENSIONS

Length: cm 8Width: cm 8Height: cm 17

Recessed depth: cm 3.4
Inclination: cm 90
Rotation: 355°

Cutout shape: SquaredWeight: cm 0.4Glow Wire Test: 650°

- Hole in false ceiling: 80x80 mm

SOURCES INCLUDED

- Category: **Led**

- Number: 1

- Watt: **9W**

Delivered lumens output: 851ImColor temperature (K): 3000K

- CRI: **=80 (min.)**

- Color Tolerance: MacAdam 4SDCM

- Efficacy: 95lm/W

Cartarilla I ZO/CK) - COPOOL

