



WEVER & DUCRÉ
LIGHTING

MILES 3.0 ROUND

317774B5

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Surface
 Jet Black
 IP20
 Interior
 365 lm
 9005^a

LED

3000 K
 CRI 90
 L80 / 50000 h
 3-step binning

OPTICAL

wide flood


PHYSICAL

Diameter 260 mm
 Height 37 mm
 1.1 kg


ELECTRICAL

phase-cut dim
 220 - 240 V
 Total connected power 8.4 W
 PC2
 Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

MILES

3.0 ROUND

317774B5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.84	0.8
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.