LED recessed spot Article no. 33265253



Light. For Generations.





Tender

recessed spot, aluminium, square. In a compact design, for installation in tool-less rapid assembly systems. Set inkl. Konverter für 230V-Netzspannung, schaltbar, Maße Konverter: L 68 x B 35 x H 21mm . Mounting method: Recessed mounting, Place of installation: Ceilingmounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6.6W, Luminous flux: 457lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, control: on/off.

Article data	
Article no.	33265253
GTIN	4250047774211
Short description	LED recessed spot
Material	Aluminium
Colour	Alu
Type of surface	Matt
Shape	Square
Built-in diameter	68 mm
Installation depth	65 mm
Length	82 mm
Width	82 mm
Weight	0.218 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 26.09.2022 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

LED recessed spot Article no. 33265253

BRUMBERG

Light. For Generations.

Lighting technology	
Colour temperature	3000 K
Light colour	White
Light output	Direct
Luminous flux	457 lm
System efficiency	69 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Beam angle	38°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	6.6 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Control	on/off

Operating technology of driver	
Current	35° mA
Protection class	U C
Degree of protection	, IP20
Power min	• V.
Power	7.2 W
Control	on/off
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. 70 ℃

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	15°
Further references	No cover with thermal insulation material
Material cover	Glass transparent

Packing data	
Gross weight	0.334 kg
Length of packaging	140 mm
Packaging width	110 mm
Packaging hight	120 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid
	that harmful substances get into the environment.

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 26.09.2022 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/